



LUND UNIVERSITY

On the Steam Reforming of Producer Gas for the Production of Clean Bio-Syngas

Standal Wangen, Espen; Malik, Azhar; Sanati, Mehri; Blekkan, Edd A

2009

[Link to publication](#)

Citation for published version (APA):

Standal Wangen, E., Malik, A., Sanati, M., & Blekkan, E. A. (2009). *On the Steam Reforming of Producer Gas for the Production of Clean Bio-Syngas*. Abstract from Norwegian Symposium on Catalysis, Trondheim, Norway.

Total number of authors:

4

General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: <https://creativecommons.org/licenses/>

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117
221 00 Lund
+46 46-222 00 00

On the steam reforming of producer gas for the production of clean bio-syngas.

Espen Standal Wangen¹, Azhar Malik², Mehri Sanati², Edd A. Blekkan¹

1. **Norwegian University of Science and Technology.** Dept. Chemical Engineering, NTNU, 7491 Trondheim.
2. **Lund University.** Ergonomics and Aerosol Technology Design Sciences, Box 118, SE-221 00 Lund, Sweden.

This study was a part of the GreenSyngas project, funded by European Commission under its 7th Framework Program. The paramount objective of this project is to develop a novel gas conditioning process to clean the raw product gas (producer gas) from the gasification of wood. The conditioning of such a gas is challenging, as it will contain an unacceptable amount of various contaminants. Gas treatment may include several steps, e.g. removal of alkali metals and particulates, sulphur species, ammonia, and higher aromatic hydrocarbons, tars.

In addition to said aromatics, the gas will contain lighter hydrocarbons. In order to maximise the production of bio-syngas, these hydrocarbons should be converted in a catalytic reformer. However, due to the high level of potential catalyst poisons, the process will require robust catalysts that are able to operate in a harsh and corrosive environment. The objective of this study was to develop a catalytic reforming system for the conversion of hydrocarbons in the producer gas.

Steam reforming of a simulated producer gas was carried out in a fixed bed steel reactor. A set of commercial nickel based steam reforming was investigated with respect to stability at close to complete hydrocarbon conversion. After 100 hours of operation, no significant drop in methane conversion was observed, although a post experiment examination of the system revealed large amounts of carbonaceous materials covering the catalyst bed.

The effect of fine particulate carbon particles deposited on steam reforming catalysts was investigated. A soot generator was employed for this purpose. The generation was based on propane combustion, and the setup offered the possibility to control particle sizes and the elemental/organic carbon ratio. The amount of deposited carbon was estimated by means of TPO. The results indicate that even small amounts of carbon (0.5 - 1.0 wt-%) could lead to a 50 % drop in initial catalyst activity.