

LUND UNIVERSITY

New methods for high-speed rail planning

Robygd, Joakim; Bastani, Mehrdad; Lindgren, Sakarias; Löwenborg, Daniel; Martin, Tina

2024

Link to publication

Citation for published version (APA): Robygd, J., Bastani, M., Lindgren, S., Löwenborg, D., & Martin, T. (2024). New methods for high-speed rail planning. Poster session presented at 84th Annual conference of the German Geophysical Conference, Jena, Germany.

Total number of authors: 5

General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors

and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights. • Users may download and print one copy of any publication from the public portal for the purpose of private study

or research.

· You may not further distribute the material or use it for any profit-making activity or commercial gain

You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: https://creativecommons.org/licenses/

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117 221 00 Lund +46 46-222 00 00







New methods for high-speed rail planning

ROBYGD, J.¹, BASTANI, M.², LINDGREN, S.³, LÖWENBORG, D.³ & T. MARTIN¹ ¹ENGINEERING GEOLOGY, LUND UNIVERSITY, ²GEOLOGICAL SURVEY OF SWEDEN, ³ARCHAEOLOGICAL DEPARTMENT, UPPSALA UNIVERSITY

Scope of the research

The project aims to increase efficiency in the pre-investigation stage of high-speed rail infrastructure (Fig. 1). The new method relies on archived data as a means for the characterization of underground conditions (Fig. 2). As a case study, a suggested railway corridor in Southern Sweden was chosen (Fig 4b). The initial steps of the methodology are:

<u>Ground suitability</u> is determined by <u>expert elicitations</u> within an analytical hierarchical \succ process (AHP) framework.



- A machine learning model (XGBoost) is trained on a well database for lithostratigraphic complexity prediction
- A machine learning model (MaxEnt) is trained on an <u>archaeological</u> database for archaeological site prediction.



Fig. 2: Graphical illustration of the method workflow.

Results & progress

Fig. 1: Example of piers for the construction of high-speed rails.

The refined data can now provide delineations of the investigated area where more detailed information of ground conditions are needed and where archaeological field efforts are to be deployed. To increase the knowledgebase the following steps are followed:

- Areas requiring additional information are rapidly mapped using <u>airborne EM</u> and GPR methods.
- > The results of the aerial screening are used for <u>updating the general model</u> and to provide a basis for an optimized ground-based investigation.
- Follow up ground-based DCIP and seismic refraction investigations.

The updated model is used for pier placements and quantification of sitespecific foundation types and reinforcements. Geotechnical drillings and soundings are carried out for model verification.

Rossion Development and the second seco



Fig 3: a) The investigation area (black bordered), and the wells used for training the machine learning model in grey points, b) Results of the AHP suitability classification after discussions and agreement within the expert group, *c*) Results of the lithostratigraphic complexity predictions, *d*) Results of the archaeological site prediction.

- All archived and public data is incorporated into a single GIS environment.
- The suitability mapping and predictive modelling for the geotechnical, geological and archaeological data has finished (Fig. 3).
- Drone based measurements with EM instrument (Fig 4a) was conducted by SGU in five areas (Fig. 4b, red spots).
- Signal sources are distant very low frequency (VLF) and LF transmitters in the frequency band 10-350 kHz.
- Measured data are used to estimate the vertical magnetic transfer functions (VMTF) in nine narrow sub-bands and then



transformed to the apparent resistivities (Fig. 4d)

- VMTFs will be 2D and 3D modelled to help detailed planning. of boreholes and pier locations.
- Maps are used for quick evaluation and detailed ground measurements.
- Ground-based DCIP and seismic measurements were conducted in three of the five aerially surveyed areas so far.

Outlook

Fig. 4: a) Photo of SGU's drone EM system; b) Overview map of the five test sites within the corridor; c) SGU Quaternary map of study area 2; d) Calculated apparent resistivities from the vertical magnetic transfer functions at different frequencies.

- Drone GPR measurements are planned for the spring as well as additional geophysical ground investigations (site 1 & 2)
- Detailed comparisons of the information gained from airborne versus ground-based data will be conducted.
- Update the overall ground classification according to the new data and adjust pier placements and reinforcements. \succ

Contact

Name: Joakim Robygd, Tina Martin E-mail: joakim.robygd@tg.lth.se, tina.martin@tg.lth.se Poster for DGG annual meeting 2024