

LUND UNIVERSITY

Direct Current-Induced Polarization Constrained by Ground Penetrating Radar for Improved Delineation of Geological Boundaries at test sites around Lake Bolmen, Sweden

Pugacheva, Polina; Martin, Tina; Günther, Thomas; Igel, Jan

2024

Document Version: Publisher's PDF, also known as Version of record

Link to publication

Citation for published version (APA):

Pugacheva, P., Martin, T., Günther, T., & Igel, J. (2024). Direct Current-Induced Polarization Constrained by Ground Penetrating Radar for Improved Delineation of Geological Boundaries at test sites around Lake Bolmen, Sweden. Poster session presented at 84th Annual conference of the German Geophysical Conference, Jena, Germany.

Total number of authors: 4

General rights

Unless other specific re-use rights are stated the following general rights apply: Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

· Users may download and print one copy of any publication from the public portal for the purpose of private study

- or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain

· You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: https://creativecommons.org/licenses/

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117 221 00 Lund +46 46-222 00 00

Direct Current-Induced Polarization Constrained by Ground Penetrating Radar for Improved Delineation of Geological Boundaries at test sites around Lake Bolmen, Sweden

P. Pugacheva¹, T. Martin², T. Günther³, J. Igel³

¹ Technical University of Munich, TUM School of Engineering and Design, Chair of Non-destructive Testing, Munich, Germany, ² Lund University, Division of Engineering Geology, Lund, Sweden, ³ Leibniz Institute for Applied Geophysics, Hanover, Germany

1. Motivation and Objective

Problem:

Brownification (brown color) of water in Lake Bolmen in Sweden arises due to the presence of higher levels of dissolved organic carbon (DOC) or iron (Fe) originating from coniferous forests and peatlands, transported through rivers, streams, and drainage. **Consequences:**

Result in an increase in drinking water treatment and harms the aquatic ecosystem [1], [2]. **Objectives:**

- Characterizing the geology and thickness of soil layers.
- Assessing the potential of using structural constraints from GPR in DCIP inversion to



2. Study Area: Lake Bolmen

- Located in South-Western Sweden.
- Twelfth largest lake in Sweden:
 - Area: 184 km²
 - Coastline length: 330 km
 - Average water depth: 6.2 m
- Geology: Dominated by granite and granitic gneiss.
- Depth to bedrock: Varies between 3 and 8 meters.
- Soil: Overlying bedrock includes peat, till, sandy till, and glaciofluvial sediments.



identify geological horizons and layers with different chargeabilities.

Fig. 1: Photo of brown water at lake Bolmen.

3. Methods



4. Results



Fig. 7: Pseudosection of apparent resistivity data from Site B, Line No. 1.



Fig. 8: Pseudosection of chargeability data from Site B, Line No. 1.



Fig. 9: Exemplary decay curves from Site B, Line No. 1.

Fig. 10: 170 MHz antenna data for Site B, Line No. 1 after processing. The reflector used for structurally-constrained inversion is shown in red.





Fig. 11: Inversion results for resisitivity (left) and chargeability data (right) with (top) and without constraints (bottom) for Site B, Line No. 1.

- Top Low Resistivity Layer: <100 Ωm, thin, heterogeneous soil layer.</p>
- Intermediate Resistivity Layer: 100-200 Ωm, different peat sequences.
- High Resistivity Layer: >600 Ωm, Granitic gneiss.
- Chargeability Anomalies: Few surface anomalies, linked to ditches.

Fig. 12: 170 MHz antenna data for Site 3, Line No. 1 after processing. The reflector used for structurally-constrained inversion is shown in red.





Fig. 13: Inversion results for resisitivity (left) and chargeability data (right) with (top) and without constraints (bottom) for Site 3, Line No. 1.

- Top High Resistivity Layer: 150-600 Ωm, heterogeneous soil layer.
- Low Resistivity Layer: 50-130 Ωm, heterogeneous.
- Chargeability Anomalies: Higher chargeability anomalies at shallow depth.

Fig. 14: 170 MHz antenna data for Site Rydan, Line No. 2 after processing. The reflector used for structurally-constrained inversion is shown in red.



- Fig. 15: Inversion results for resisitivity (left) and chargeability data (right) with (top) and without constraints (bottom) for Site Rydan, Line No. 2.
- Top Resistivity Layer: 120-300 Ωm, heterogeneous soil layer.
- High Resistivity Layer: 300-2000 Ωm, very heterogeneous, likely glaciofluvial sediments and till.
- Chargeability Anomalies: Higher chargeability values starting from the surface and continuing to a depth of ca. 2.5 meters.

5. Conclusions

In the majority of sites integrating reflectors from GPR data into the mesh enhanced the

6. Future Work

• To enhance further interpretation, it is recommended to improve the analysis by incorporating

- precision of delineating the DCIP boundary between bedrock and soil, as well as distinguishing between various chargeability layers.
- Some high-chargeability anomalies have been found to be associated with the location of ditches.
- The first information about the hydrogeological system regarding the bedrock depth and soil thickness could be better obtained through the structurally-constrained inversion model.
- data from soil and water samples, as well as boreholes.

85.3

- Continuous monitoring of the different riparian zones with geophysical (DCIP) and hydrological methods.
- Model the hydrogeological system in the Lake Bolmen area, the interaction of groundwater with surface water (especially with drainage ditches), and surrounding soils.
- An optimized riparian zone design in terms of size and structure.

7. Acknowledgements

This research was supported as part of Blue Transition, an Interreg North Sea project co-funded by the European Union. This work got also funding from the FORMAS Blue Innovation project (2021-02657) and Sweden Water Research.

We are grateful to Ankita Prayag, Torleif Dahlin, Yaman Ahmad Abu Jaish, Clemens Klante, Nicola Zaru and Ethan Hiss for their invaluable help in conducting the DCIP and GPR field measurements.

8. References

[1] Albrecht, E., Hannonen, O., Palacín-Lizarbe, C., Suni, J., Härkönen, L.H., Soininen, N., Kukkonen, J. and Vainikka, A., 2023. Browning of boreal lakes: Do public perceptions and governance meet the biological foundations?. Ecological Applications, p.e2856.

[2] Klante, C., Hägg, K. and Larson, M., 2022. Understanding short-term organic matter fluctuations to optimize drinking water treatment. Water Practice & Technology, 17(10), pp.2141-2159.

[3] Martin T, Günther T, Orozco AF, Dahlin T. Evaluation of spectral induced polarization field measurements in time and frequency domain. Journal of Applied Geophysics. 2020 Sep 1;180:104141.

[4] Favaro, M., 2021. Assessment of Groundwater Flow to Lake Bolmen. Master Thesis, Lund University.









Blue Transition