



LUND UNIVERSITY

Assimilating hydraulic response data from in-situ bioremediation injection treatment for improved decision-support modelling

Benavides Höglund, Nikolas; Sparrenbom, Charlotte J.; Hugman, Rui

Published in:

36th nordic geological winter meeting, Göteborg, January 10–12 2024, Abstract volume

2024

Document Version:

Publisher's PDF, also known as Version of record

[Link to publication](#)

Citation for published version (APA):

Benavides Höglund, N., Sparrenbom, C. J., & Hugman, R. (2024). Assimilating hydraulic response data from in-situ bioremediation injection treatment for improved decision-support modelling. In C. Regnéll, T. Zack, K. Holme, & J. Andersson (Eds.), *36th nordic geological winter meeting, Göteborg, January 10–12 2024, Abstract volume: Geologiska Föreningen Specialpublikation* (Vol. 5, pp. 39-39)

Total number of authors:

3

General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: <https://creativecommons.org/licenses/>

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117
221 00 Lund
+46 46-222 00 00

Assimilating hydraulic response data from in-situ bioremediation injection treatment for improved decision-support modelling

Nikolas Benavides Höglund^a, Carlotte Sparrenbom^b and Rui Hugman^c

^aDepartment of Geology, Lund University, Lund, Sweden, nikolas.hoglund@geol.lu.se; ^bDepartment of Geology, Lund University, Lund, Sweden, charlotte.sparrenbom@geol.lu.se; ^cINTERA, Perth, Australia, rhugman@intera.com

In-situ remediation through the injection of bioremediation fluids is becoming increasingly common for treating contaminated sites. Contaminants are targeted for treatment either directly at the source zone or through injections that form a permeable reactive barrier to prevent further transport of the contaminants. Commonly, multiple injections are performed in a grid covering an area of strategic importance. These injections, essentially serving as high-frequency inverse pumping tests, present an opportunity to capture rich information regarding the hydraulic response (changes in head during injection) in the aquifer at multiple locations. This information, which is often overlooked, can add valuable insight into the site, improve site characterization, aiding in predictions of future management actions and enhancing future monitoring efforts. However, due to the high pressures during injections, hydraulic fracturing often occurs at the time the injections are made. These events, representing temporary or permanent changes in aquifer properties depending on the treatment strategy, must be considered when assimilating hydraulic response data into a decision-support model to reduce the risk of introducing parametric biases. We have developed four groundwater numerical models for a PCE-contaminated site in Alingsås, Sweden, that was treated with in-situ remediation injections in 2017. Each model, although structurally identical, is calibrated using different parameterization and weighting approaches applied to the hydraulic response data. Preliminary results showed that by employing time-varying parameters at the location and time of injection, the model achieved a better fit with measured data and a lower parameter variance compared to other models. On the other hand, traditionally configured models (i.e., models that do not employ the use of time-varying parameters) show signs of parameter compensation, potentially biasing any predictions based upon their use.