



LUND UNIVERSITY

The Sea Swift Experiments October 1974 : Parts 1-4

Källström, Claes

1975

Document Version:

Publisher's PDF, also known as Version of record

[Link to publication](#)

Citation for published version (APA):

Källström, C. (1975). *The Sea Swift Experiments October 1974 : Parts 1-4*. (Technical Reports TFRT-7078). Department of Automatic Control, Lund Institute of Technology (LTH).

Total number of authors:

1

General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: <https://creativecommons.org/licenses/>

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117
221 00 Lund
+46 46-222 00 00

THE SEA SWIFT EXPERIMENTS
OCTOBER 1974.

PART II

C. KÄLLSTRÖM

Report 7516(C) June 1975
Department of Automatic Control
Lund Institute of Technology

TABLE OF CONTENTS

Page

PART I

1. Introduction	1
2. Measurement Equipment	3
3. The Adaptive Autopilot	5
3.1. The straight course keeping regulator	6
3.2. The yaw regulator	7
4. Computer Programs	11
5. Discussion of the Experiments	13
5.1. The straight course keeping experiments	13
5.2. The yawing experiments	22
5.3. The experiments for identification	23
6. Conclusions	25
7. Acknowledgements	28
8. References	29
APPENDIX A - Notations	30
APPENDIX B - Program Listings	36
APPENDIX C - Experiments	45
A1	55
A2	69
A3	84
A4	96
A5	108
A6	120
A7	133
A8	146
A9	159
A10	172
A11	185
A12	201
A13	214
A14	227
A15	242
A16	255

	<u>Page</u>
PART II	
A17	268
A18	281
A19	294
A20	309
A21	323
A22	336
A23	349
A24	362
A25	375
A26	388
A27	401
A28	414
A29	427
A30	440
A31	453
A32	466
A33	479
A34	494
A35	507
A36	520
PART III	
A37	533
A38	548
A39 A	563
A39 B	579
A40	594
A41	625
A42	642
A43	658
A44	673
A45	688
B1	703
B2	721

Page

B3	740
B4	758
B5	775
B6	794

PART IV

B7	811
B8	829
B9	830
B10	847
B11	868
B12	887
B13	906
B14	926
B15	943
C1	962
C2	973
C3	984
D1	996
D2	1007
E1	1018
E2	1032
E3	1047
E4	1061

THE SEA SWIFT EXPERIMENTS,
OCTOBER 1974 - PART II

Claes Källström

EXPERIMENT A17

Date 1974-10-14
 Time 19.06
 Duration 27 min
 Position N 09° 07' E 53° 26'
 Water depth deep
 Forward draught 20.2 m
 Aft draught 20.2 m
 Wind direction SW (1; see Appendix A)
 Wind velocity 1 Beaufort (1-1.5 m/s, light air)
 Wave height 1 m (rollings)
 PSIREF 208°
 Rudder limit Not active

Regulator structure

NA = 3 NB = 1 NC = 1 K = 8
 IREG = 10 IRDIF = 0 RL = 0.98 IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -15.448 \\ 25.557 \\ -9.928 \\ 0.845 \\ -3.271 \end{bmatrix} \quad P = \begin{bmatrix} 4.372 & & & & \\ -6.843 & 12.163 & & & \\ 2.867 & -5.735 & 3.129 & & \\ -0.059 & 0.079 & -0.017 & 0.015 & \\ 9.035 & -8.878 & -0.767 & -0.109 & 97.368 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = 0.181$$


Statistics (mean value and standard deviation)

DELTA	1.21 ± 1.98 deg
PSI-PSIREF	-0.017 ± 0.544 deg
AN	85.65 ± 0.58 rpm
U	15.29 ± 0.25 knots


$$V_1 = 0.835$$

$$V_2 = 0.688$$


PLOT HP A17P1(1) ZERO -5 7 DELCOC DEG




PLOT A17P1(3) ZERO -5 7 ° DELTAS DEG




PLOT A17P1(4) ZERO -5 7 °DELTA DEG




PLOT R17P1(5) ZERO -0.1 0.1 -PP DEG/S




PLOT A17P1(6) 04 88 °RN RPM



PL0T R17P1(7) 14 16 "U KNOTS



PLOT R17P1(8) @ 1 -VI KNOTS



TIME (H)

50.

40.


30.

20.


10.

0.

PL0T A17P1(8) 0 1 -V2 KNOTS




PLOT R17P1(10) ZERO -0.1 0.1 °R DEG/S




TIME (H)
50.

PLOT R17P1(13 14) 206 210 °PSI PSIREF DEG



PLOT R17P2 -20 40 °REGULATOR PARAMETERS



EXPERIMENT A18

Date 1974-10-14
 Time 22.04
 Duration 27 min
 Position N 08° 18' E 53° 12'
 Water depth deep
 Forward draught 20.2 m
 Aft draught 20.2 m
 Wind direction SW (1; see Appendix A)
 Wind velocity 2 Beaufort (2-3.5 m/s, light breeze)
 Wave height 2 - 3 m (rollings)
 PSIREF 207.5° (Sailmaster)
 Rudder limit Not active

Regulator structure

NA = 3 NB = 1 NC = 1 K = 5
 IREG = 15 IRDIF = 0 RL = 0.98 IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -16.325 \\ 26.380 \\ -10.022 \\ 1.034 \\ -1.195 \end{bmatrix} \quad P = \begin{bmatrix} 2.566 & & & & \\ -3.199 & 5.634 & & & \\ 1.077 & -2.671 & 2.096 & & \\ -0.021 & 0.027 & -0.006 & 0.001 & \\ 4.247 & -6.009 & 0.880 & 0.063 & 55.943 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = 0.033$$


Statistics (mean value and standard deviation)

DELTA	-1.06 ± 1.87 deg
PSI-PSIREF	-0.059 ± 0.167 deg
AN	86.13 ± 0.28 rpm
U	16.20 ± 0.11 knots


$$V_1 = 0.493$$

$$V_2 = 0.381$$


PILOT HP A18P(1) ZERO -5 7 DELCOC DEG




PLOT R10P1(3) ZERO -5 7 "DELTA" DEG




PLOT A18P1(4) ZERO -5 7 °DELTA DEG




PLUT #10P1(S) ZERO -0.1 0.1 -PP DEG/S



PL0T R1CP1(6) 84 88 -AN RPM



FLOY A10:1(7) 15 17 -U KNOTS



PLOT RIOP1(8) @ 1 -VI KNOTS



TIME (H)

50.

40.

30.

20.

10.

0.

PLOT A18P1(S) 9 1 -V2 KNOTS

0.75

0.5

0.25

0.



TIME (M)

50.

40.


30.

20.


10.

0.


PLOT A16P1(16) ZERO -0.1 0.1 "R DEC/S



FLOT A16P1 (13 14) 286 208 °PSI PSIREF DEG



PLOT A10P2 -20 40 REGULATOR PARAMETERS



EXPERIMENT A19

Date	1974-10-14
Time	23.00
Duration	30 min
Position	N 08° 04', E 53° 06'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	2 Beaufort (2-3.5 m/s, light breeze)
Wave height	2 - 3 m (rollings)
PSIREF	207.6° (Sailmaster)
Rudder limit	Not active

Regulator structure

NA = 3	NB = 1	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.98	IRR = 2 BR = 0.2

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -17.159 \\ 28.051 \\ -10.999 \\ 1.036 \\ -0.560 \end{bmatrix} \quad P = \begin{bmatrix} 4.178 & & & & \\ -5.070 & 7.545 & & & \\ 1.146 & -2.741 & 1.855 & & \\ -0.020 & 0.024 & -0.004 & 0.001 & \\ 31.256 & -34.852 & 5.513 & -0.086 & 413.370 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.107$$


Statistics (mean value and standard deviation)

DELTA	-0.23 ± 1.86 deg
PSI-PSIREF	0.054 ± 0.247 deg
AN	85.78 ± 0.25 rpm
U	16.17 ± 0.06 knots


$$V_1 = 0.415$$

$$V_2 = 0.410$$


PLOT HP A19P1(1) ZERO -7 5 °DELCO DEG




PLOT A1SP1(3) ZERO -7 6 "DELTA" DEG



PLOT A1SP1(4) ZERO -7 5 °DELTA DEG



PLOT A19P1(S) ZERO -0.1 0.1 "PP DEG/S



PLOT A1SP1(7) 15 17 -U KNOTS

16.5

16.

15.5

15.



TIME (M)

50.

40.


30.

20.


10.

0.


PLOT R1SP1(S) 84 83 "AN RPM




PLOT #19P1 (e) 1 "V1 KNOTS




PLOT A1SP1(S) @ 1 -V2 KNOTS




PLOT A18P1(16) ZERO -0.1 0.1 °R DEG/S




PLOT R18P1(11) ZERO -0.1 0.1 "AVR DEG/S (BR-0.2)




PLOT A19P1(12) ZERO -0.1 0.1 -DPSIDT DEG/S (IDPSI=5)



PLOT A1SP1(13 14) 207 208 °PSI PSIREF DEG



PLOT A19P2 - 20 40 REGULATOR PARAMETERS



EXPERIMENT A20

Date 1974-10-15
 Time 01.13
 Duration 32 min
 Position N 07° 30' E 53° 00'
 Water depth deep
 Forward draught 20.2 m
 Aft draught 20.2 m
 Wind direction SW (1; see Appendix A)
 Wind velocity 2 Beaufort (2-3.5 m/s, light breeze)
 Wave height 2 - 3 m
 PSIREF 208.1°, 208.2° (Sailmaster)
 Rudder limit Not active (0-15 min)
 ±10° (15-32 min)

Regulator structure

0 - 15 min: Kockums' PID-regulator

$$k_P = 1.0 \quad k_D = 123 \text{ s} \quad k_I = 1/123 \text{ s}^{-1} \quad T_s = 15 \text{ s}$$

15 - 32 min: AUTP1

$$\begin{array}{llll}
 \text{NA} = 3 & \text{NB} = 1 & \text{NC} = 1 & \text{K} = 5 \\
 \text{IREG} = 15 & \text{IRDIF} = 0 & \text{RL} = 0.98 & \text{IRR} = 1
 \end{array}$$

Final values (AUTP1)


$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -14.171 \\ 20.518 \\ -7.202 \\ 0.837 \\ -11.302 \end{bmatrix} \quad \text{P unknown}$$

$$a_1 + a_2 + a_3 = -0.855$$


Statistics (mean value and standard deviation)

	<u>0-15 min (PID)</u>	<u>15-32 min (AUTP1)</u>
DELTA	0.32 ± 0.63 deg	-0.01 ± 2.61 deg
PSI-PSIREF	0.033 ± 0.140 deg	0.509 ± 0.771 deg
AN	85.87 ± 0.20 rpm	85.87 ± 0.46 rpm
U	16.46 ± 0.20 knots	16.40 ± 0.11 knots
V ₁	0.071	1.535
V ₂	0.060	1.535


PLOT MP A20P1(1) ZERO -20 20 "DELCOC DEG




PLOT HP A20P1(2) ZERO -10 10 "DELCON DEG




PLOT A20P1(3) ZERO -10 10 "DELTA" DEG




PLOT A26P1(4) ZERO -10 10 "DELTA DEG




PLOT A20P1(5) ZERO -0.1 0.1 "PP DEG/S




PLOT R20P1 (6) 04 09 "RN RPM



PLOT RZGP1(7) 16 17 "U KNOTS




PLOT RZEP1 (8) 0 1 -V1 KNOTS




TIME (H)


PLOT R26P1(8) @ 1 -V2 KNOTS




PLOT AZOP1(10) ZERO -0.1 0.1 "R DEG/S



PLOT A26P1(13 14) 207 211 -PSI PSIREF DEG



PLOT A20P2 -20 40 "REGULATOR PARAMETERS



EXPERIMENT A21

Date	1974-10-15
Time	08.54
Duration	40 min
Position	N 05° 33' E 52° 14'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	2 Beaufort (2-3.5 m/s, light breeze)
Wave height	1 - 2 m (light sea from SW)
PSIREF	209°
Rudder limit	Not active

The aft doppler log was adjusted during the experiment, which affected the V2-measurement.

Regulator structure

NA = 3	NB = 1	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.98	IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -10.640 \\ 15.967 \\ -5.930 \\ 0.679 \\ 16.434 \end{bmatrix} \quad P = \begin{bmatrix} 3.853 & & & & \\ -6.171 & 11.999 & & & \\ 2.595 & -6.314 & 4.116 & & \\ 0.021 & -0.132 & 0.112 & 0.018 & \\ 5.922 & -6.322 & -0.094 & -0.029 & 92.124 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.603$$


Statistics (mean value and standard deviation)

DELTA	-0.22 ± 0.91 deg
PSI-PSIREF	-0.122 ± 0.207 deg
AN	85.81 ± 0.27 rpm
U	16.04 ± 0.12 knots


$$V_1 = 0.145$$

$$V_2 = 0.141$$


PLOT HP A21P1(1) ZERO -5 7 -DELCOG DEG




PLOT A2IP1(3) ZERO -5 7 "DELTA" DEG




PLOT A21P1(4) ZERO -6 7 "DELTA DEG




PLOT A21P1(5) ZERO -0.1 0.1 -PP DEG/S




PLOT A21P1(6) 64 68 -AN RPH




PLOT A21P1(7) 15 17 "U KNOTS



PLOT A21P1(8) Q 1 -V1 KNOTS




PLOT A21P1(9) ZERO -0.6 0.4 "V2 KNOTS




PLOT A21P1(10) ZERO -0.1 0.1 °R DEG/S

0.05 0.0 -0.05 -0.1




TIME (M) 0. 10. 20. 30. 40. 50.

PLOT A21P1 (13 14) 200 210 "PSI PSIREF DEG



PLOT A21P2 -14 26 "REGULATOR PARAMETERS



EXPERIMENT A22

Date	1974-10-15
Time	09.45
Duration	36 min
Position	N 05° 21' E 52° 07'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	2 Beaufort (2-3.5 m/s, light breeze)
Wave height	1 - 2 m
PSIREF	209°
Rudder limit	Not active

The aft doppler log was adjusted during the experiment, which affected the V2-measurement.

Regulator structure

NA = 3	NB = 1	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.97	IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -12.708 \\ 19.647 \\ -7.066 \\ 0.670 \\ 3.836 \end{bmatrix} \quad P = \begin{bmatrix} 5.915 & & & & \\ -8.712 & 17.106 & & & \\ 3.641 & -9.595 & 6.928 & & \\ 0.035 & -0.161 & 0.150 & 0.020 & \\ 8.260 & -8.057 & -1.517 & 0.093 & 140.644 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.127$$


Statistics (mean value and standard deviation)

DELTA	-0.17 ± 0.85 deg
PSI-PSIREF	-0.091 ± 0.217 deg
AN	85.86 ± 0.27 rpm
U	16.29 ± 0.17 knots


$$V_1 = 0.131$$

$$V_2 = 0.128$$


PLOT HP A22P1(1) ZERO -5 7 "DELCOC DEG




PLOT A22P1 (3) ZERO -5 7 "DELTA" DEG



PLOT A22P1(4) ZERO -5 7 "DELTA DEG



PLOT R22P1(5) ZERO -0.2 0.2 "PP DEG/S




PLOT A22P1(6) 04 00 "AN RPM

87.

86.

85.

84.



TIME (M)
50.

40.

30.

20.

10.

0.

PLOT R22P1 (7) 15 17 "U KNOTS




15.
15.5
16.
16.5


0. 10. 20. 30. 40. 50.

TIME (M)


PLOT R22P1(8) 0 1 "V1 KNOTS




PLOT R22P1(9) ZERO -0.5 0.5 "V2 KNOTS




PLOT A22P1(10) ZERO -0.1 0.1 °R DEG/S



PLOT A22Pi (13 14) 208 210 "PSI PSIREF DEG



PLOT A22P2 - 14 26 "REGULATOR PARAMETERS



EXPERIMENT A23

Date	1974-10-15
Time	10.54
Duration	17 min
Position	N 05° 02' E 51° 58'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	2 Beaufort (2-3.5 m/s, light breeze)
Wave height	1 - 2 m
PSIREF	209°
Rudder limit	Not active

Regulator structure

NA = 3	NB = 1	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.99	IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -13.563 \\ 20.540 \\ -7.076 \\ 0.662 \\ 2.719 \end{bmatrix} \quad P = \begin{bmatrix} 2.400 & & & & \\ -3.215 & 6.306 & & & \\ 1.166 & -3.471 & 2.770 & & \\ 0.005 & -0.061 & 0.066 & 0.007 & \\ 3.654 & -4.871 & 0.901 & 0.026 & 43.533 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.099$$


Statistics (mean value and standard deviation)

DELTA	-0.40 ± 0.91 deg
PSI-PSIREF	-0.034 ± 0.167 deg
AN	85.84 ± 0.26 rpm
U	16.33 ± 0.16 knots


$$V_1 = 0.128$$

$$V_2 = 0.112$$


PLOT HP A23P1(1) ZERO -5 7 DELCOC DEG




PLOT A23P1 (3) ZERO -5 7 °DELTAS DEG




PLOT A23P1(4) ZERO -5 7 "DELTA DEG




PLOT A23P1(6) ZERO -0.1 0.1 *PP DEG/S




PLOT A23P1(6) 04 00 "AN RPM




PLOT R23P1(7) 15 17 °U KNOTS




PL0T R23P1 (8) 8 1 "V1 KNOTS




PL0T A23P1(9) ZERO -0.5 0.5 "V2 KNOTS



PLOT A23P1(10) ZERO -6.1 0.1 "R DEG/S



PLOT A23P1(13 14) 208 210 "PSI PSIREF DEG



EXPERIMENT A24

Date	1974-10-15
Time	13.34
Duration	30 min
Position	N 04 ^o 26' E 51 ^o 38'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	2 Beaufort (2-3.5 m/s, light breeze)
Wave height	1 - 2 m
PSIREF	209 ^o
Rudder limit	Not active

Regulator structure


NA = 2	NB = 1	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.98	IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -4.554 \\ 4.147 \\ 0.888 \\ 30.925 \end{bmatrix} \quad P = \begin{bmatrix} 0.789 & & & \\ -0.781 & 0.817 & & \\ -0.029 & 0.029 & 0.006 & \\ 4.425 & -4.862 & -0.118 & 61.401 \end{bmatrix}$$

$$a_1 + a_2 = -0.407$$

PLOT A23P2 -14 26 "REGULATOR PARAMETERS




Statistics (mean value and standard deviation)

DELTA	0.29 ± 1.78 deg
PSI-PSIREF	-0.510 ± 0.555 deg
AN	85.59 ± 0.38 rpm
U	16.14 ± 0.11 knots


$$V_1 = 0.893$$


$$V_2 = 0.885$$

PLOT WP R24P1(1) ZERO -7 G "DELCOG DEG




FLOT R24P1(3) ZERO -7 6 "DELTA" DEG






PLOT AZIMP(6) ZERO -0.1 0.1 PP DEG/S




PLOT RZHP1(7) 15 17 ~U KNOTS




TIME (M)


PLOT A24P1(6) 04 68 "DN RPN




PLOT 024P1(0) 0 1 -VI KIOTS




FLOT R24P1(8) ZERO -0.5 0.5 -V2 KNOTS



PLOT R24P1(10) ZERO -0.1 0.1 °R DEG/S



PLOT A24P1(13 14) 207 211 °PSI PSIPREF DEG



FLOT A24P2 -20 40 REGULATOR PARAMETERS



EXPERIMENT A25

Date	1974-10-15
Time	14.31
Duration	26 min
Position	N 04 ^o 13' E 51 ^o 31'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	2 Beaufort (2-3.5 m/s, light breeze)
Wave height	1 - 2 m
PSIREF	209 ^o
Rudder limit	Not active

Regulator structure

NA = 3	NB = 2	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.98	IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \\ c_1 \end{bmatrix} = \begin{bmatrix} -14.112 \\ 21.221 \\ -7.715 \\ 0.654 \\ 0.025 \\ -0.588 \end{bmatrix} \quad P = \begin{bmatrix} 3.714 \\ -3.107 & 10.445 \\ 0.241 & -7.804 & 8.124 \\ -0.127 & -0.408 & 0.538 & 0.054 \\ -0.103 & -0.375 & 0.485 & 0.045 & 0.049 \\ 1.914 & -3.132 & 1.465 & 0.133 & 0.237 & 53.165 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.606$$


Statistics (mean value and standard deviation)

DELTA	0.21 ± 1.10 deg
PSI-PSIREF	-0.003 ± 0.171 deg
AN	85.55 ± 0.21 rpm
U	16.30 ± 0.08 knots


$$V_1 = 0.155$$

$$V_2 = 0.150$$


PLOT HP A26P1(1) ZERO -5 7 DELCOC DEC




PLOT A25P1(3) ZERO -5 7 DELTAS DEG



PLOT A2SP1(4) ZERO -5 7 -DELTA DEG






FLOT R125P1(6) 04 00 °PM RPH

84.
85.
87.




0.
10.
20.
30.
40.
50.
TIME (M)


PLOT A2SP1(7) 16 17 "U KNOTS




PLOT A28P1(9) 0 1 -V1 KNOTS




PLOT R2SP1(8) ZERO -0.5 0.5 ^V2 KNOTS




PLOT R25P1(10) ZERO -0.1 0.1 -R DEG/S



PLOT A25P1(13 14) 208 210 -PSI PSIREF DEG



PLOT A25P2 -14 26 REGULATOR PARAMETERS



EXPERIMENT A26

Date	1974-10-15
Time	16.20
Duration	26 min
Position	N 03 ^o 48' E 51 ^o 12'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	3 Beaufort (4-5.5 m/s, gentle breeze)
Wave height	2 m
PSIREF	209 ^o
Rudder limit	Not active

Regulator structure

NA = 3	NB = 2	NC = 2	K = 5
IREG = 15	IRDIF = 0	RL = 0.98	IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \\ c_1 \\ c_2 \end{bmatrix} = \begin{bmatrix} -13.790 \\ 21.190 \\ -7.316 \\ 0.686 \\ 0.018 \\ -2.277 \\ 0.112 \end{bmatrix} \quad P = \begin{bmatrix} 5.758 & & & & & & \\ -8.857 & 27.467 & & & & & \\ 4.861 & -22.273 & 20.833 & & & & \\ 0.140 & -1.174 & 1.206 & 0.099 & & & \\ 0.135 & -1.077 & 1.107 & 0.084 & 0.083 & & \\ 4.980 & -7.260 & 2.224 & 0.283 & 0.163 & 75.302 & \\ -2.338 & 7.221 & -5.993 & 0.041 & 0.075 & 12.069 & 63.850 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = 0.084$$


Statistics (mean value and standard deviation)

DELTA	-0.34 ± 0.89 deg
PSI-PSIREF	-0.001 ± 0.140 deg
AN	85.55 ± 0.24 rpm
U	16.32 ± 0.09 knots


$$V_1 = 0.110$$

$$V_2 = 0.099$$


PLOT HP A2CP1(1) ZERO -4 4 DELCOC DEC




PLOT A2SP1(3) ZERO -4 4 "DELTA" DEG



PLOT R26P1(4) ZERO -4 4 "DELTA DEG



PLOT A2SP1(5) ZERO -0.1 0.1 "PP DEC/S



FLOT R2SP1(6) 54 88 *AN RPH


TIME (M)

84.
85.
86.
87.


0.
10.
20.
30.
40.
50.




FL0T A20P1(7) 15 17 -U KNOTS




PLOT A2SP1(0) @ 1 -V1 KNOTS




PLOT A2CP1(0) ZERO -0.5 0.6 *V2 KNOTS




PLOT A2SP1(10) ZERO -0.1 0.1 °R DEC/S



PLOT A2SP1(13 14) 200 210 °PSI PSIREF DEG



PLOT A26P2 -14 26 "REGULATOR PARAMETERS



EXPERIMENT A27

Date	1974-10-15
Time	18.58
Duration	33 min
Position	N 03° 12' E 50° 51'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	2 - 3 Beaufort (2-5.5 m/s, light to gentle breeze)
Wave height	1 - 2 m
PSIREF	209°
Rudder limit	Not active

Regulator structure

NA = 4	NB = 1	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.98	IRR = 1

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ a_4 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -12.034 \\ 17.518 \\ -4.728 \\ -1.337 \\ 0.467 \\ -3.039 \end{bmatrix} \quad P = \begin{bmatrix} 4.809 & & & & & & \\ -6.943 & 48.538 & & & & & \\ 3.299 & -70.648 & 118.547 & & & & \\ -0.356 & 30.878 & -55.218 & 27.190 & & & \\ 0.040 & -2.951 & 5.103 & -2.371 & 0.246 & & \\ 7.065 & -21.429 & 24.290 & -10.183 & 1.009 & 91.117 & \end{bmatrix}$$

$$a_1 + a_2 + a_3 + a_4 = -0.581$$


Statistics (mean value and standard deviation)

DELTA	0.17 ± 0.74 deg
PSI-PSIREF	0.005 ± 0.153 deg
AN	85.52 ± 0.26 rpm
U	15.92 ± 0.09 knots


$$V_1 = 0.081$$

$$V_2 = 0.078$$


PLOT MP A27P1(1) ZERO -4 4 "DELCOG DEG




PLOT A27P1(3) ZERO -4 4 °DELTA DEG




PLOT A27P1(4) ZERO -4 4 "DELTA DEG




PLOT R27P1(5) ZERO -0.1 0.1 "PP DEG/S



PLOT R27P1(6) 54 60 -FM RPM



PLOT A27P1(7) 15 17 ~U KNOTS



PLOT A27P1(9) 0 1 "VI KNOTS



TIME (M)
50.

40.


30.

20.


10.

0.


PLOT RZ7P1(9) ZERO -0.5 0.5 -V2 KNOTS




PLOT A27P1(10) ZERO -0.1 0.1 "R DEG/S



PLOT R27P1(13 14) 200 210 °PSI PSIREF DEG



PLOT A2773 -14 26 "REGULATOR PARAMETERS"



EXPERIMENT A28

Date	1974-10-16
Time	07.57
Duration	21 min
Position	N 00° 06' E 49° 10'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SW (1; see Appendix A)
Wind velocity	3-4 Beaufort (4-8 m/s, gentle to moderate breeze)
Wave height	4 m
PSIREF	208°
Rudder limit	Not active

Regulator structure

NA = 3 NB = 2 NC = 0 K = 4
 IREG = 20 RL = 0.98

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \end{bmatrix} = \begin{bmatrix} -5.815 \\ 8.792 \\ -2.997 \\ 0.480 \\ 0.162 \end{bmatrix} \quad P = \begin{bmatrix} 2.316 & & & & \\ -2.846 & 6.999 & & & \\ 0.996 & -5.081 & 4.934 & & \\ -0.255 & -0.163 & 0.479 & 0.152 & \\ -0.009 & -0.599 & 0.683 & 0.080 & 0.152 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.020$$


Statistics (mean value and standard deviation)

DELTA	1.55 ± 0.95 deg
PSI-PSIREF	0.033 ± 0.226 deg
AN	85.60 ± 0.25 rpm
U	15.67 ± 0.05 knots


$$V_1 = 0.383$$

$$V_2 = 0.142$$


PLOT MP A26P1(1) ZERO -4 4 DELCOC DEG




PLOT A28P1(3) ZERO -4 4 °DELTA DEG




PLOT A26P1(4) ZERO -4 4 °DELTA DEG




PLOT R28P1(5) ZERO -0.1 0.1 -PP DEG/S




PLOT R28P1(6) 84 88 -AN RPM




PLOT R26P1(7) 15 17 °U KNOTS




PLOT_A28P1(8) @ 1 -V1 KNOTS




PLOT A20P1(9) ZERO -0.5 0.5 -U2 KNOTS




PLOT A26P1(10) ZERO -0.1 0.1 °R DEG/S



PLOT A28PI(13 14) 287 289 -PSI PSIREF DEG



PLOT A20P2 -15 15 REGULATOR PARAMETERS



EXPERIMENT A29

Date	1974-10-16
Time	09.12
Duration	32 min
Position	S 00° 09' E 49° 02'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	S (8; see Appendix A)
Wind velocity	3-4 Beaufort (4-8 m/s, gentle to moderate breeze)
Wave height	4 m
PSIREF	208°
Rudder limit	Not active

Probably misleading measurements of U, V1 and V2 due to air-bubbles below the doppler logs.

Regulator structure

NA = 3 NB = 2 NC = 0 K = 5
 IREG = 15 RL = 0.98

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \end{bmatrix} = \begin{bmatrix} -9.280 \\ 13.473 \\ -4.185 \\ 0.966 \\ 0.562 \end{bmatrix} \quad P = \begin{bmatrix} 2.540 & & & & \\ -3.550 & 7.286 & & & \\ 1.533 & -4.426 & 3.621 & & \\ -0.021 & -0.127 & 0.177 & 0.032 & \\ -0.002 & -0.153 & 0.177 & 0.022 & 0.030 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = 0.008$$


Statistics (mean value and standard deviation)

DELTA	1.48 ± 1.03 deg
PSI-PSIREF	0.001 ± 0.260 deg
AN	85.62 ± 0.28 rpm
U	6.36 ± 0.36 knots


$$V_1 = 0.393$$

$$V_2 = 0.174$$


PLOT R29P1(6) 64 88 "RM RPM




PLOT HP R23P1(1) ZERO -4 4 DELCOC DEG




PLOT R29P1(3) ZERO -4 4 "DELTA" DEG




PLOT A29P1(4) ZERO -4 4 DELTA DEC




PLOT A2SP1(6) ZERO -0.2 G.2 -PP DEG/S




PLOT A29P1(7) 6 7 "U KNOTS







PLOT R29P1(9) ZERO -1 : -VZ KNOTS




PLOT A29P1(10) ZERO -0.1 0.1 "R DEC/S



PLOT A29P1(13 14) 297 299 "PSI PSIREF DEC



PLOT A29P2 -15 15 REGULATOR PARAMETERS



EXPERIMENT A30

Date	1974-10-16
Time	14.06
Duration	31 min
Position	S 01 ^o 20' E 48 ^o 23'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SSW (1; see Appendix A)
Wind velocity	3-4 Beaufort (4-8 m/s, gentle to moderate breeze)
Wave height	3 - 4 m
PSIREF	208 ^o
Rudder limit	Not active

Regulator structure

NA = 3	NB = 1	NC = 0	K = 5
IREG = 15	RL = 0.98		

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \end{bmatrix} = \begin{bmatrix} -12.381 \\ 18.843 \\ -6.589 \\ 1.079 \end{bmatrix} \quad P = \begin{bmatrix} 2.842 & & & & \\ -4.235 & 7.573 & & & \\ 1.900 & -3.935 & 2.532 & & \\ -0.031 & 0.044 & -0.016 & 0.004 & \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.127$$


Statistics (mean value and standard deviation)

DELTA	1.38 ± 1.37 deg
PSI-PSIREF	-0.024 ± 0.253 deg
AN	85.67 ± 0.26 rpm
U	20.24 ± 0.09 knots


$$V_1 = 0.443$$

$$V_2 = 0.252$$


PLOT HP R3SP1(1) ZERO -4 4 "DELCOG DEC




PLOT AOSP1(3) ZERO -4 4 "DELTA" DEG




FLOT R30P1(4) ZERO -4 4 "DELTA DEG




PLOT R30P1(5) ZERO -0.2 0.2 °PP DEG/S




PLOT R3CP1 (6) 84 88 "AH RPH




PLOT A30P1(8) 0.5 1.5 "V1 KNOTS




PLOT A30P1(7) 19 21 "U KNOTS




PLOT A36P1(S) ZERO -0.6 0.5 -V2 KNOTS




PLOT A30P1(10) ZERO -0.1 0.1 "R DEG/S



PLOT A36PI (13 14) 207 209 °PSI PSIREF DEG



PLOT A30P2 -14 20 REGULATOR PARAMETERS




Statistics (mean value and standard deviation)

DELTA	1.57 ± 0.91 deg
PSI-PSIREF	-0.063 ± 0.171 deg
AN	85.65 ± 0.25 rpm
U	18.64 ± 0.09 knots


$$V_1 = 0.363$$

$$V_2 = 0.116$$


PLOT HP A31P1(1) ZERO -4 4 "DELCOC DEG




PLOT A31P1(3) ZERO -4 4 "DELTAS DEG




PLOT A31P1(4) ZERO -4 4 "DELTA DEC




PLOT R31P1(5) ZERO -0.1 0.1 *PP DEG/S



PLOT R31P1(8) 24 88 -RM RPM



PLOT R31P1(7) 18 20 "U KNOTS



PLOT R31P1(8) 0.5 1.5 "V1 KNOTS

1.25

0.75

0.5



TIME (M)

50.

40.


30.

20.


10.

0.


PLOT R31P1(9) ZERO -0.5 0.5 "V2 KNOTS




PLOT R31P1(10) ZERO -0.1 0.1 "R DEG/S



PLOT R31P1(13 14) 207 209 °PSI PSIREF DEG



PLOT A31P2 -15 15 -REGULATOR PARAMETERS



EXPERIMENT A32

Date 1974-10-17
 Time 09.13
 Duration 20 min
 Position S 05° 48' E 46° 04'
 Water depth deep
 Forward draught 20.2 m
 Aft draught 20.2 m
 Wind direction SE (7; see Appendix A)
 Wind velocity 4 Beaufort (6-8 m/s, moderate breeze)
 Wave height 5 m
 PSIREF 208°
 Rudder limit Not active

Regulator structure

NA = 3 NB = 2 NC = 0 K = 5
 IREG = 15 RL = 0.99

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \end{bmatrix} = \begin{bmatrix} -13.014 \\ 20.353 \\ -7.757 \\ 0.645 \\ 0.327 \end{bmatrix} \quad P = \begin{bmatrix} 0.549 & & & & \\ -0.840 & 1.846 & & & \\ 0.371 & -1.132 & 0.869 & & \\ -0.003 & -0.030 & 0.036 & 0.005 & \\ 0.002 & -0.036 & 0.037 & 0.003 & 0.005 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.418$$


Statistics (mean value and standard deviation)

DELTA	1.65 ± 2.01 deg
PSI-PSIREF	-0.003 ± 0.405 deg
AN	85.99 ± 0.33 rpm
U	7.89 ± 1.83 knots


$$V_1 = 0.840$$

$$V_2 = 0.568$$


PLOT HP R32P1(1) ZERO -7 5 "DELCOC DEG




PLOT R32P1(13 14) 207 209 °PSI PSIREF DEG




PLOT A32P1(3) ZERO -7 5 -DELTA DEG







PLOT R32P1(6) ZERO -0.1 0.1 "PP DEG/S




PLOT R32P1(6) 84 88 "RN RPH




PLOT R32P1(7) 6 12 "U KNOTS




PLOT R32P1(8) ZERO -0.5 0.5 "V1" KNOTS



PLOT A32P1(8) ZERO -0.5 1.5' "V2 KNOTS




PL0T A32P1(10) ZERO -0.1 0.1 °R DEG/S



TIME (M)

PLOT A32P2 -15 15 "REGULATOR PARAMETERS



EXPERIMENT A33

Date	1974-10-17
Time	10.56
Duration	30 min
Position	S 06° 06' E 45° 59'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SE (7; see Appendix A)
Wind velocity	4 Beaufort (6-8 m/s, moderate breeze)
Wave height	4 - 5 m
PSIREF	208°
Rudder limit	Not active

Regulator structure

NA = 3	NB = 1	NC = 1	K = 5
IREG = 15	IRDIF = 0	RL = 0.98	IRR = 3 IDPSI = 5

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ c_1 \end{bmatrix} = \begin{bmatrix} -10.302 \\ 16.913 \\ -6.688 \\ 0.367 \\ 3.424 \end{bmatrix} \quad P = \begin{bmatrix} 3.999 & & & & \\ -5.027 & 7.921 & & & \\ 1.810 & -3.620 & 2.487 & & \\ 0.017 & -0.092 & 0.101 & 0.013 & \\ 21.433 & -26.568 & 7.357 & 0.053 & 172.894 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.077$$


Statistics (mean value and standard deviation)


DELTA	1.71 ± 1.36 deg
PSI-PSIREF	0.028 ± 0.239 deg
AN	86.11 ± 0.22 rpm
U	10.77 ± 0.93 knots

$$V_1 = 0.535$$


$$V_2 = 0.243$$


PLOT HP A33P1(1) ZERO -4 4 "DELCOC DEG






PLOT R33P1(9) ZERO -1 1 -V2 KNOTS







PLOT A33P1(5) ZERO -0.2 0.2 "PP DEG/S




PLOT A33P1(6) 84 88 "AN RPM




PLOT R33P1(7) 9 13 "U KNOTS




PLOT R33P1(8) ZERO -0.5 0.5 "V1 KNOTS




PLOT A33P1(10) ZERO -0.1 0.1 °R DEG/S




PLOT R33PI(11) ZERO -0.1 0.1 "AVR DEG/S (BR=0.2)




PLOT R33P1(12) ZERO -0.1 0.1 "DPSIDT DEG/S (IDPSI=5)



PLOT R33P1(13 14) 207 208 "PSI PSIREF DEG



PLOT A33P2 - 15 15 "REGULATOR PARAMETERS



EXPERIMENT A34

Date	1974-10-17
Time	14.20
Duration	33 min
Position	S 07° 04' E 45° 26'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SE (7; see Appendix A)
Wind velocity	4 Beaufort (6-8 m/s, moderate breeze)
Wave height	4 - 5 m
PSIREF	208°
Rudder limit	Not active

Regulator structure

NA = 3 NB = 2 NC = 0 K = 4
 IREG = 20 RL = 0.98

Final values

$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \end{bmatrix} = \begin{bmatrix} -9.729 \\ 13.809 \\ -4.053 \\ 0.828 \\ 0.667 \end{bmatrix} \quad P = \begin{bmatrix} 1.234 & & & & \\ -1.427 & 2.924 & & & \\ 0.455 & -1.724 & 1.620 & & \\ -0.038 & 0.007 & 0.035 & 0.007 & \\ 0.008 & -0.073 & 0.074 & 0.003 & 0.008 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = 0.027$$


Statistics (mean value and standard deviation)

DELTA	1.89 ± 1.54 deg
PSI-PSIREF	-0.072 ± 0.250 deg
AN	86.05 ± 0.24 rpm
U	16.91 ± 0.23 knots


$$V_1 = 0.662$$

$$V_2 = 0.305$$


PLOT HP A34P1<1> ZERO -5 7 "DELCOC DEC




PLOT R34P1(3) ZERO -5 7 "DELTA" DEG




PLOT A34P1(4) ZERO -5 ? "DELTA DEC




PLOT R34P1(5) ZERO -0.2 0.2 "PP DEG/S




PLOT A34P1(6) 64 88 "AN RPH




PLOT R34P1(7) 16 18 "U KNOTS




PLOT A34P1(8) ZERO -0.5 0.5 "V1 KNOTS




PLOT A34P1(9) ZERO -1 1 "V2 KNOTS




PLOT A34P1(10) ZERO -0.1 0.1 "R DEG/S



PLOT A34P1(13 14) 207 209 °PSI PSIREF DEG



PLOT A34P2 -15 15 REGULATOR PARAMETERS



Statistics (mean value and standard deviation)

DELTA	1.75 ± 1.66 deg
PSI-PSIREF	0.001 ± 0.283 deg
AN	86.14 ± 0.28 rpm
U	17.01 ± 0.20 knots

$$V_1 = 0.662$$

$$V_2 = 0.356$$

EXPERIMENT A35

Date	1974-10-17
Time	15.46
Duration	28 min
Position	S 07° 25' E 45° 15'
Water depth	deep
Forward draught	20.2 m
Aft draught	20.2 m
Wind direction	SE (7; see Appendix A)
Wind velocity	4 Beaufort (6-8 m/s, moderate breeze)
Wave height	4 - 5 m
PSIREF	208°
Rudder limit	Not active

Regulator structure


NA = 3 NB = 2 NC = 0 K = 5
 IREG = 15 RL = 0.99

Final values


$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \end{bmatrix} = \begin{bmatrix} -11.569 \\ 15.763 \\ -4.783 \\ 0.894 \\ 0.568 \end{bmatrix} \quad P = \begin{bmatrix} 0.544 & & & & \\ -0.745 & 1.740 & & & \\ 0.257 & -1.055 & 0.871 & & \\ -0.001 & -0.032 & 0.035 & 0.004 & \\ 0.004 & -0.035 & 0.033 & 0.003 & 0.004 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.589$$


PLOT HP A35PI(1) ZERO -5 7 "DELCOC DEG




PLOT A36P1 (3) ZERO -5 7 "DELTA" DEG




PLOT R35P1(4) ZERO -5 7 "DELTA DEG




PLOT A35P1(6) 64 00 -AN RPH




PLOT R35P1(5) ZERO -0.2 0.2 "PP DEG/S




PLOT R36P1(7) 16 18 "U KNOTS




PLOT A35P1(8) ZERO -0.5 0.5 "V1 KNOTS




PLOT A35P1(8) ZERO -0.5 0.5 "V2 KNOTS




PLOT A3581(10) ZERO -0.1 0.1 "R DEC/S



PLOT A35P1(13 14) 207 209 PSI PSIREF DEG



PLOT A36P2 -15 15 "REGULATOR PARAMETERS



Statistics (mean value and standard deviation)

	<u>0-45 min</u>	<u>5-45 min</u>
DELTA	1.68 ± 1.77 deg	1.66 ± 1.45 deg
PSI-PSIREF	-0.001 ± 0.321 deg	0.005 ± 0.219 deg
AN	86.03 ± 0.30 rpm	86.05 ± 0.25 rpm
U	16.55 ± 0.24 knots	16.55 ± 0.24 knots
V ₁	0.699	0.534
V ₂	0.416	0.258

EXPERIMENT A36

Date 1974-10-17
 Time 17.29
 Duration 45 min
 Position S 07° 54' E 44° 58'
 Water depth deep
 Forward draught 20.2 m
 Aft draught 20.2 m
 Wind direction SE (7; see Appendix A)
 Wind velocity 3 Beaufort (4-5.5 m/s, gentle breeze)
 Wave height 3 - 4 m
 PSIREF 208°
 Rudder limit Not active

Regulator structure


NA = 3 NB = 2 NC = 0 K = 5
 IREG = 15 RL = 0.99

Final values


$$\begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ b_1 \\ b_2 \end{bmatrix} = \begin{bmatrix} -11.357 \\ 16.107 \\ -4.851 \\ 0.902 \\ 0.576 \end{bmatrix} \quad P = \begin{bmatrix} 0.567 & & & & \\ -0.702 & 1.611 & & & \\ 0.251 & -1.031 & 0.938 & & \\ 0.000 & -0.030 & 0.035 & 0.004 & \\ 0.004 & -0.032 & 0.032 & 0.002 & 0.003 \end{bmatrix}$$

$$a_1 + a_2 + a_3 = -0.101$$


PLOT HP A3SP1(1) ZERO -10 10 "DELCOC DEG




PLOT R36P1(3) ZERO -10 10 "DELTA" DEC




PLOT R3CP1(4) ZERO -10 10 °DELTA DEG



PLOT A36P1(6) ZERO -0.2 0.2 -PP DEG/S




PLOT R36P1(6) 84 88 "AN RPH



2

PLOT A36P1(9) ZERO -0.5 0.5 "V2 KNOTS



PLOT A36PI (13 14) 206 210 °PSI PSIREF DEG

