## **ERRATA**

## Compact and Efficient Millimetre-Wave Circuits for Wideband Applications

Lars Ohlsson

November 4, 2015

**Preface, p. xv:** "... Mar. 2015, submitted." status of Paper II should read "... Oct. 2015, revision submitted." as of «major revision» decision on May 23, 2015

**Preface, p. xvi:** "... Apr. 2015, submitted." status of Paper VII should read "... vol. 51, no. 21, pp. 1671–1673, Oct. 2015." as the paper has been published

**Chapter 3, p. 25:** "... $g_{min} = -4.88 \text{-mS}/\mu\text{m}^2$ ..." is incorrect and should read "... $g_{min} = -5.78 \text{-mS}/\mu\text{m}^2$ ..." as resulted from the fitted model and utilised in calculations

**Appendix B, p. 81:** (printed version only) "... transit-charge per unit area,  $q_{\rm trc} = \tau_{\rm trc} g_{\rm res}$ , of the RTD is approximated by the resonant-tunnelling conductance per unit area,  $g_{\rm res} = \partial J_{\rm res}/\partial V_{\rm CE}$ , and..." is incorrect and should read "... transit-charge per unit area,  $q_{\rm trc} = -\tau_{\rm trc} J_{\rm res}$ , of the RTD is approximated by the resonant-tunnelling current density,  $J_{\rm res}$ , and..." as utilised in the model