



LUND UNIVERSITY

Nonequivalent cascaded convolutional codes obtained from equivalent constituent convolutional encoders

Höst, Stefan; Johannesson, Rolf; Zyablov, Viktor V.

Published in:

[Host publication title missing]

DOI:

[10.1109/ISIT.1998.708943](https://doi.org/10.1109/ISIT.1998.708943)

1998

[Link to publication](#)

Citation for published version (APA):

Höst, S., Johannesson, R., & Zyablov, V. V. (1998). Nonequivalent cascaded convolutional codes obtained from equivalent constituent convolutional encoders. In *[Host publication title missing]* (pp. 338) <https://doi.org/10.1109/ISIT.1998.708943>

Total number of authors:

3

General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: <https://creativecommons.org/licenses/>

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117
221 00 Lund
+46 46-222 00 00

Nonequivalent Cascaded Convolutional Codes Obtained from Equivalent Constituent Convolutional Encoders¹

Stefan Höst and Rolf Johannesson
Dept. of Information Technology
Lund University
P.O. Box 118
S-221 00 Lund, Sweden
stefanh@it.lth.se, rolf@it.lth.se

Viktor V. Zyablov
Inst. for Problems of Information Transmission
of the Russian Academy of Science
B. Karetnyi per., 19, GSP-4
Moscow, 101447 Russia
zyablov@ippi.ras.ru

Abstract — Cascaded convolutional codes with conventional convolutional codes as constituent codes are powerful and attractive to use in communication systems where very low error probabilities are needed. This paper clearly demonstrates the dramatic effect the replacement of the inner convolutional encoder by an equivalent one could have on the cascaded convolutional code.

I. INTRODUCTION

The cascade of two convolutional encoders without an interleaver but with matched rates is a cascade of a rate $R_o = b_o/c_o$ outer encoder of memory m_o and a rate $R_i = b_i/c_i$ inner encoder of memory m_i , where $b_i = c_o$. The cascaded convolutional code C_c is encoded by the rate $R_c = R_o R_i = b_o/c_i \stackrel{\text{def}}{=} b_c/c_c$ convolutional encoder of memory $m_c \leq m_o + m_i$.

Let the information sequence $u^c(D)$ of the cascaded rational encoder $G^c(D)$ be encoded as the cascaded code-word $v^c(D)$,

$$v^c(D) = u^c(D)G^c(D) = u^c(D)G^o(D)G^i(D), \quad (1)$$

where $G^o(D)$ and $G^i(D)$ are the rational generator matrices of the outer and inner encoders, respectively.

II. NONEQUIVALENT CASCADED ENCODERS FROM EQUIVALENT CONSTITUENT ENCODERS

Let

$$G^{c'}(D) = G^{o'}(D)G^{i'}(D) \quad (2)$$

be the generator matrix of the cascaded convolutional code, where $G^{o'}(D) = T^o(D)G^o(D)$ and $G^{i'}(D) = T^i(D)G^i(D)$. We show that $G^{c'}(D)$ and $G^c(D) = G^o(D)G^i(D)$ are, in general, not equivalent.

If only the outer generator matrix $G^o(D)$ is replaced by an equivalent generator matrix $G^{o'}(D)$, then the new cascaded generator matrix $G^{c'}(D)$ will be equivalent to the cascaded generator matrix $G^c(D)$.

Since it is the code sequences from the outer encoder that serve as information sequences for the inner encoder,

the cascaded convolutional code is a proper (assuming $R_o < 1$) subset of the inner convolutional code, $C^c \subset C^i$. Replacing the inner encoder with an equivalent inner encoder changes the mapping from the inner information sequences to the inner code sequences and, therefore, also the subset of the inner convolutional code. In general, we will obtain a different cascaded convolutional code when we replace the inner encoder by an equivalent one. This fact will be illustrated by examples. We also notice that since $C^c \subset C^i$, catastrophicity of the inner generator matrix does not imply catastrophicity of the generator matrix for the cascade.

Can the inner generator matrix be chosen such that we obtain the same cascaded convolutional code, i.e., such that $G^{c'}(D)$ is equivalent to $G^c(D)$? Indeed it can, which will be illustrated by a simple example. If $G^{c'}(D)$ and $G^c(D)$ are equivalent generator matrices, then for some invertible $b_o \times b_o$ matrix $S(D)$

$$G^{c'}(D) = G^o(D)T(D)G^i(D) = S(D)G^c(D). \quad (3)$$

III. SYSTEMATIC CASCADED ENCODERS FROM SYSTEMATIC CONSTITUENT ENCODERS

From basic encoding matrices we can easily obtain equivalent rational systematic encoding matrices,

$$G_{\text{sys}}^c(D) = G_{\text{sys}}^o(D)G_{\text{sys}}^i(D), \quad (4)$$

where $G_{\text{sys}}^o(D)$, and $G_{\text{sys}}^i(D)$ are systematic equivalents to $G^o(D)$ and $G^i(D)$, respectively. In general, the systematic encoding matrix $G_{\text{sys}}^c(D)$ is not equivalent to $G^c(D) = G^o(D)G^i(D)$.

If $G^o(D)$ and $G^i(D)$ are minimal, then a minimal realization of $G_{\text{sys}}^c(D)$ has at most the same number of delay elements as the cascaded encoder $G^c(D)$ has when realized as a cascade of the two minimal encoders $G^o(D)$ and $G^i(D)$.

REFERENCES

- [1] S. Höst, R. Johannesson, V. R. Sidorenko, K. Sh. Zigangirov, and V. V. Zyablov, "Cascaded convolutional codes", in *Communications and Coding Research Studies Press Ltd. and John Wiley & Sons*, 1998, pp. 10-29.
- [2] S. Höst, R. Johannesson, and V. V. Zyablov, "Nonequivalent Cascaded Convolutional Codes Obtained from Equivalent Constituent Convolutional Encoders", submitted to *Problemy Peredachi Inform.*

¹This research was supported in part by the Swedish Research Council for Engineering Sciences under Grant 94-83 and in part by the Royal Swedish Academy of Sciences in liaison with the Russian Academy of Sciences.