



LUND UNIVERSITY

Wideband 60-GHz Stacked Microstrip Antenna on PTFE Substrate

Bondarik, Alexander; Sjöberg, Daniel

2014

[Link to publication](#)

Citation for published version (APA):

Bondarik, A., & Sjöberg, D. (2014). *Wideband 60-GHz Stacked Microstrip Antenna on PTFE Substrate*. Abstract from GigaHertz/AntennEMB, Gothenburg, Sweden.

Total number of authors:

2

General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: <https://creativecommons.org/licenses/>

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117
221 00 Lund
+46 46-222 00 00

Wideband 60-GHz Stacked Microstrip Antenna on PTFE Substrate

Alexander Bondarik, Daniel Sjöberg
Lund University, Department of Electrical and Information Technology
P.O. Box 118, S-221 00 Lund, Sweden
alexander.bondarik@eit.lth.se

I. INTRODUCTION

A microstrip antenna stacked design with complex radiating patch on top is proposed to overcome the wideband requirements for 60-GHz communication systems [1]. The antenna is fabricated on multilayer PTFE substrate and has a planar structure which radiates in a broadside direction. The designed antenna has improved return loss characteristic compared to existing microstrip antenna stacked designs for 60 GHz [2], [3]. Return loss, radiation pattern, and gain measurement results are in good agreement with simulation results obtained using CST Microwave Studio.

II. RESULTS

The microstrip antenna is built using two layers of PTFE (polytetrafluoroethylene) Taconic TLY-5 substrate ($\epsilon_r = 2.2$) and prepreg Taconic CuClad 6700 ($\epsilon_r = 2.17$). On the bottom there is a microstrip line that feeds a single rectangular patch using aperture coupling through the slot in the ground plane. On the top, there is a parasitic patch of complex form. The parasitic patch is coupled electromagnetically with the rectangular patch. Vias are not used in the design. An end launch connector was used in the antenna measurements. The antenna parameters were measured using 67 GHz Agilent E836A PNA. Radiation pattern measurements were performed using a rotary stage in a room with scattering environment. A standard horn antenna connected to a low-noise amplifier was used to register a signal from the microstrip antenna. A gain-transfer method was used to estimate the antenna realized gain.

The measured 10-dB return loss bandwidth is from 54 GHz up to 66 GHz and fully covers the unlicensed band around 60 GHz. Radiation patterns in E-plane and in H-plane are stable for 57 GHz to 64 GHz.

The Measured microstrip antenna realized gain is from about 6.5 dBi for 57 GHz up to about 8.5 dBi for 64 GHz. Measured characteristics are in good agreement with simulation.

III. CONCLUSIONS

A stacked microstrip antenna for 60-GHz communication systems was designed, fabricated, and measured. The measured return loss bandwidth fully satisfies the communication standard requirements. Radiation pattern and antenna gain are stable inside the communication band.

The designed antenna is suitable for 60-GHz high speed wireless communication system.

REFERENCES

- [1] T.S. Rappaport, J.N. Murdock, and F. Gutierrez, "State of the art in 60-GHz integrated circuits and systems for wireless communications," *Proc. IEEE*, vol.99, no. 8, pp. 1390-1436, Aug. 2011.
- [2] T. Seki, N. Honma, K. Nishikawa, K. Tsunekawa, "Millimeter-wave high-efficiency multilayer parasitic microstrip antenna array on teflon substrate," *IEEE Trans. Antennas Propag.*, vol. 53, no. 6, pp. 2101-2106, June 2005.
- [3] W. Hong, K.-H. Baek, and A. Goudelev "Multi-layer antenna package for IEEE 802.11ad employing ultralow-cost FR4," *IEEE Trans. Antennas Propag.*, vol. 60, no. 10, pp. 5932-5938, Dec. 2012.