



LUND UNIVERSITY

Investigation and Comparison Between Radiation Center and Phase Center for Canonical Antennas

Ehrenborg, Casimir; Fridén, Jonas; Kristensson, Gerhard

2015

[Link to publication](#)

Citation for published version (APA):

Ehrenborg, C., Fridén, J., & Kristensson, G. (2015). *Investigation and Comparison Between Radiation Center and Phase Center for Canonical Antennas*. Abstract from Progress in Electromagnetics Research Symposium (PIERS), 2015, Prague, Czech Republic.

Total number of authors:

3

General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: <https://creativecommons.org/licenses/>

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117
221 00 Lund
+46 46-222 00 00

Investigation and Comparison Between Radiation Center and Phase Center for Canonical Antennas

Casimir Ehrenborg¹, Jonas Fridén², and Gerhard Kristensson¹

¹ Department Electrical and Information Technology Lund University, Box 118, SE-221 00 Lund, Sweden,
e-mail: {casimir.ehrenborg, gerhard.kristensson}@eit.lth.se

² Ericsson Research, Ericsson AB, Gothenburg, Sweden,
email: jonas.friden@ericsson.com

The radiation center was introduced by Fridén and Kristensson in [1]. The need to define this parameter arose from the ambiguity of the phase center definition. The phase center is traditionally calculated by manually selecting a region in the main lobe of the radiation pattern, and minimizing the phase of the co-polarized field component. The choice of angular region to use is not obvious, and automatic calculation of beam width is hard to implement as a robust numerical algorithm. In contrast, the radiation center algorithm presented in [1] provides a unique point corresponding to the minimum of the squared angular momentum of the field.

This presentation investigates results from radiation center and phase center calculations for canonical antennas with frequencies varying inside their operational bands. The two methods are compared and evaluated against the expected phase center positions and the radiation center is investigated as a replacement parameter to the phase center. In [1] the radiation center was calculated using measured data with unknown errors in the absolute position of the antenna in the coordinate system. Therefore, in this study the concept is applied to simulated far-field patterns wherein the position of the antenna is known.

References

- [1] J. Friden and G. Kristensson. Calculation of antenna radiation center using angular momentum. *Antennas and Propagation, IEEE Transactions on*, **61**(12), 5923–5930, Dec 2013.