

LUND UNIVERSITY

Climate benefits from alternative energy uses of biomass plantations in Uganda

Zanchi, Giuliana; Frieden, Dorian; Pucker, Johanna; Bird, David Neil; Buchholz, Thomas; Windhorst, Kai

Published in: Biomass & Bioenergy

DOI: 10.1016/j.biombioe.2012.03.023

2013

Link to publication

Citation for published version (APA): Zanchi, G., Frieden, D., Pucker, J., Bird, D. N., Buchholz, T., & Windhorst, K. (2013). Climate benefits from alternative energy uses of biomass plantations in Uganda. *Biomass & Bioenergy, 59*, 128-136. https://doi.org/10.1016/j.biombioe.2012.03.023

Total number of authors: 6

General rights

Unless other specific re-use rights are stated the following general rights apply: Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

· Users may download and print one copy of any publication from the public portal for the purpose of private study

or research.
You may not further distribute the material or use it for any profit-making activity or commercial gain

· You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: https://creativecommons.org/licenses/

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117 221 00 Lund +46 46-222 00 00

1	CLIMATE BENEFITS FROM ALTERNATIVE ENERGY USES OF BIOMASS
2	PLANTATIONS IN UGANDA
3	
4	Giuliana Zanchi ^a *, Dorian Frieden ^a , Johanna Pucker ^a , Neil Bird ^a , Thomas Buchholz ^b , Kai
5	Windhorst ^c
6	
7	^a JOANNEUM RESEARCH Forschungsgesellschaft mbH, Leonhardstraße 59, 8010 Graz,
8	Austria
9	^b The Rubenstein School of Environment and Natural Resources, University of Vermont, 81
10	Carrigan Drive, Burlington, VT 05405, USA
11	^c UNIQUE forestry consultants Ltd, Schnewlinstraße 10, 79098 Freiburg, Germany
12	
13	*Corresponding author:
14	E-mail: giuliana.zanchi@nateko.lu.se
15	Tel: +43 316 876 1422; Fax: +43 316 8769 1422
16	
17	Present Address of corresponding author:
18	Department of Earth and Ecosystem Sciences
19	Division of Physical Geography and Ecosystem Analysis
20	Lund University
21	Sölvegatan 12, SE-223 62 Lund, Sweden
22	

25 The establishment of tree plantations in rural areas in Uganda could provide renewable energy 26 to rural communities, while decreasing greenhouse gas emissions from conventional 27 electricity sources and unsustainable forest use. The study evaluates the greenhouse gas 28 benefits that could be produced by biomass based energy systems in Anaka, a rural settlement 29 in the Amuru district in northern Uganda. Two alternative energy uses are explored: a) 30 electricity production through wood gasification and b) traditional fuelwood use. It is 31 estimated that a small-scale wood gasifier could provide electricity for basic community 32 services by planting less than 10 hectares of new short rotation coppices (SRCs). The 33 gasification system could save 50-67% of the GHG emissions produced by traditional diesel based electricity generators in terms of CO₂-eq. (0.61-0.83 t MWh⁻¹ or 7.1 t y⁻¹ per hectare of 34 35 SRCs). It was also estimated that traditional use of fuelwood in households is currently 36 unsustainable, i.e. the consumption of wood is higher than the annual growth from natural 37 wood resources in the study area. It is estimated that 0.02-0.06 ha per capita of plantations 38 could render the current consumption of wood sustainable. In this way, the CO₂ emissions 39 produced through unsustainable extraction of wood could be avoided (2.0-7.3 t per capita per year or 50-130 t y^{-1} per hectare of SRCs). 40

41

42 KEYWORDS:

Bioenergy; Gasification; GHG Balance; Sustainability; Uganda; Short Rotation Coppice
44

45 1 INTRODUCTION

46

47 Biomass is the main source of energy in Uganda. National statistics report that 91.5% of 48 energy consumption is derived from the combustion of biomass sources such as fuelwood, 49 charcoal and residues. A very limited share of energy use is covered by electricity (1.1%) and 50 the remaining 7.4% is produced by fossil fuels [1]. 51 Wood biomass will likely remain the dominant household energy source for cooking and 52 heating for several decades in Uganda due to low accessibility to alternative energy sources 53 [2]. In addition, biomass is seen as an option to provide electricity to rural areas where only 54 1% of the population has access to the grid. High electricity prices, frequent power outages, 55 and high line losses pose hurdles to increasing access to the grid over the short to medium 56 term. 57 At the same time, forest statistics report that wood resources in Uganda are constantly 58 decreasing [3]. Consequently, biomass based electricity generation or traditional energy from 59 fuelwood can be expected to be constrained by a decreasing availability of wood from forests 60 and other wooded lands. By contributing to the degradation of natural wood resources, 61 biomass based energy also contributes to increase greenhouse gas (GHG) emissions in the 62 atmosphere and to climate change. 63 The establishment of new plantations in developing countries could guarantee wood 64 availability for the future, supply feedstock to renewable energy systems that are accessible to 65 rural communities and produce GHG benefits as compared to fossil fuel based systems and 66 unsustainable wood extraction. 67 This study assesses the climate mitigation benefits produced by alternative uses of wood 68 plantations, when new Short Rotation Coppices (SRCs) are established on non-forested, low

69 carbon-stock land in Uganda. The comparison of GHG benefits from alternative uses of a

- 70 certain bioenergy source is important to support the most efficient strategies to achieve GHG
- emission reductions [4] [5]. To the knowledge of the authors, this is the first attempt to make
- such an assessment from wood plantations in Uganda.

73 Two alternative energy uses of wood plantations in a rural area in Uganda are considered:

- a) Electricity from wood gasification; and
- b) Firewood for traditional use in households.
- 76 The climate mitigation benefits of wood gasification are assessed by applying a GHG balance

based on a Life Cycle Assessment methodology. The balance compares the GHG impacts of

the gasifier to the impacts of a typical fossil fuel based electricity generation.

79 In parallel, we assessed the area of SRC plantations needed to supply fuelwood to the rural

80 community. The plantations would avoid degradation of natural biomass resources and thus

81 avoid increasing GHG in the atmosphere. An estimate of the avoided emissions is provided.

83 2 METHODS

84

85 2.1 STUDY AREA

87 The study area is located in the Amuru district in the Northern part of Uganda ($02^{\circ}36'0''N$, 88 31°57'0"E). The CLIMWAT database [6] reports an annual precipitation of about 1,500 mm y^{-1} and an average annual temperature of 23°C for the meteorological station in Gulu. 89 90 Climatic measurements taken in 2005-2007 in Aswa-Lolim, Amuru suggest that the average 91 rainfall could be lower in certain areas of the Amuru district, around 900 to 1,000 mm per 92 annum. [7]. 93 The Anaka refugee camp in Amuru is the settlement chosen for the installation of the gasifier 94 and the assessment of the impacts of traditional use of fuelwood. The Anaka internally 95 displaced people camp (IDP camp) hosts about 22,450 people. Main electricity users in the 96 camp are the hospital and shops. Anaka is located in the north-western part of a water catchment in which the main land uses are grasslands (727 km²), followed by agricultural land 97 (214 km²) and forests (192 km²) [8]. Currently, grasslands are used for hunting. Most likely, 98 99 in the near future land will return to small holder agriculture and cattle ranching, as they were 100 before the civil war. 101 102 2.2 **BIOMASS FOR ELECTRICITY** 103 104 Previous investigations showed that small-scale wood gasifiers could be an economically and 105 socially feasible energy system to produce electricity in rural Uganda [9]. This study 106 integrates previous analysis by assessing the mitigation potential of wood gasifiers in Uganda. The GHG benefits of electricity generation by wood gasification as compared to electricity 107

originating from diesel generators in the IDP camp of Anaka are evaluated through a GHGbalance based on a Life Cycle Assessment methodology.

110

111 2.2.1 GHG BALANCE

112

113 A GHG balance, based on a Life Cycle Assessment (LCA) methodology, includes all

114 processes, which influence GHG emissions from *cradle to grave* [10]. The GHGs included in

the study are carbon dioxide (CO_2), methane (CH_4) and nitrous oxide (N_2O). Global Warming

116 Potentials (GWP) on a 100 year time horizon are used to express the contribution of CO₂, CH₄

and N_2O to global warming in terms of equivalent amount of $CO_2(CO_2-eq.)$ [11].

118 The GHG balance is performed with the Global Emission Model of Integrated Systems

119 (GEMIS), version 4.5 [12] and project specific data are added to the GEMIS standard data set

120 version 4.5. Two different systems for electricity production are analysed:

- "Electricity wood gasifier E-WG": Production of electricity with a centralized wood
 gasification system. The biomass used is supplied from Short Rotation Coppices
- 123 (SRCs) of *Eucalyptus grandis* Hill ex Maiden.
- "Electricity diesel generator E-DG": Production of the electricity with decentralized
 diesel generators.

126 The GHG balance is based on process chains which are designed for each investigated

127 system: the wood gasification and the reference fossil fuel system (diesel generator). A

128 process chain describes the complete life cycle, starting with the production of raw materials

and ending with the supply of energy to the end user (Figure 1). Emissions or removals from

130 the conversion of grassland to SRCs are also included.

131

132 Figure 1

133

134 2.2.2 INPUT DATA

135

136 The electricity demand for the Anaka camp is estimated based on a study conducted in the 137 refugee camp of Kyangwali, Uganda within the project BIOSYRCA [13]. Electricity is used by the hospital and the trading centre of the Anaka camp. In Kyangwali, the electricity 138 demand is estimated to be 25.5 MWh y^{-1} . In this study, a demand of 30 MWh y^{-1} is assumed 139 140 as a conservative estimate to include a possible increase of demand in the near future and 141 higher electricity needs for the hospital. 142 The data on the electricity generators are reported in Table 1. The gasifier powers a modified 143 diesel engine that runs on a dual fuel mode. The fuel gas provides 75% of the primary energy 144 input.. Diesel is required for start-up operations and to support the systems. A small power 145 grid must be constructed to supply electricity from the gasifier to the main buildings of the 146 refugee camp. The length of transmission lines is assumed to be 2 km to connect the hospital 147 and shops of the trading centre. In the case of diesel generators each of the buildings that 148 require electricity is equipped with a separate diesel generator. 149 150 Table 1 ^aType Ankur Gasifier WBG-15/GAS-9; data according to [14] and expert judgment. 151 152 ^bDecentralized units in the main buildings type PRAMAC P4500-PF322SYA; data according 153 to product specification (www.pramac.com) 154

155 The wood for gasification is supplied by Short Rotation Coppices (SRCs) of *E. grandis*. It is

assumed that the plantation density is 2.5×2.5 m or equal to a stem density of 1600 ha^{-1} the

maximum rotation length is 6 years [15] and that the annual productivity of the stands ranges between 5 to 15 t ha⁻¹ y⁻¹ on an oven dry basis [13]. It is also assumed that the productivity of the plantations corresponds to the biomass that can be harvested.

160 The total planted area needed for the SRCs is calculated based on the productivity of the 161 plantations and the total amount of wood required by the gasification system. The lower heating value of wood is assumed equal to 18 GJ t^{-1} and the electrical conversion efficiency 162 15% [13]. It is calculated that a wood supply of 30 t y^{-1} is needed to produce an electricity 163 output of 30 MWh y⁻¹ from the gasifier, if wood contributes to 75% of the energy input of the 164 dual-mode system. By assuming an annual productivity of 5 to 15 t $ha^{-1} y^{-1}$, the final harvest 165 produces 30-90 t ha⁻¹. Therefore the annual demand is met by harvesting 1.0 to 0.33 hectares 166 167 each year. To guarantee a constant annual supply of wood, a total area of 2.0 to 6.0 ha needs 168 to be converted to Eucalyptus plantations and 1/6 of it is cut every year.

Plantations should be established on areas not used for agricultural production in order toexclude competition with other major land uses, primarily food production. Therefore, the

171 SRCs are planted on an area currently covered by grasslands.

The annual emissions from planting and harvesting are calculated as an average over 20 years, 172 173 taking into account that harvesting starts in year six and that the plantations are renewed every 174 three rotation periods. The transport emissions are assessed by assuming a maximum distance 175 of 30 km between the plantations and the gasifier. The emissions caused by transportation for 176 planting and harvesting are calculated based on a daily productivity of a team of 3 to 6 177 workers. It is assumed that each worker plants 220 seedlings per day and harvests 120 trees per day. The fuel consumption of the truck is assumed to be at 0.165 dm³ km⁻¹, i.e. 9.9 dm³ d⁻¹ 178 ¹. The harvesting is done with chainsaws. A fuel consumption of 12.8 dm^3 and an oil 179 consumption of 2.9 dm³ per working day are assumed. The emissions caused by use of 180 181 herbicide and fertilizer before planting are also included. It is assumed that a manual chipping

182	system is used to chip the wood used for the gasifier. Motor driven chippers are very
183	effective, but they require a substantial initial investment, besides constant service and
184	maintenance. Hand operated or spring activated scissors or axes were considered a more
185	suitable option in rural Uganda.
186	An inventory table of the inputs and outputs of the gasification system is reported in the
187	Appendix.
188	
189	2.2.3 LAND USE CHANGE EMISSIONS AND REMOVALS
190	
191	The carbon (C) stock changes due to the conversion of grasslands to Eucalyptus plantations
192	are included in the GHG balance. The change is calculated as the difference between the
193	carbon stock of the Eucalyptus plantations and the carbon stock of grasslands on hectare
194	basis. The annual change over a conversion period of 20 years is considered [11]:
195	(1) $\Delta C = \frac{(C_E - C_R)}{20}$
196	Where:
197	ΔC : carbon stock change due to land use change (t ha ⁻¹ y ⁻¹)
198	C_E : carbon stock in Eucalyptus SRCs (t ha ⁻¹)
199	C_R : carbon stock in grasslands (t ha ⁻¹)
200	
201	Only the carbon stock changes in the biomass are included in the calculation. The conversion
202	of cropland or grassland to plantations will likely increase or maintain unaltered the amount
203	of carbon in soils [16]. Therefore, it is conservatively assumed that the carbon stock changes
204	in the soil are equal to zero [11]. The biomass carbon content of grasslands is derived from

205 IPCC default values (8 t ha⁻¹ of C). The biomass in the SRCs is assessed based on a stand

206productivity of 5-15 t ha⁻¹ and an IPCC default root-to-shoot ratio of 0.24 to convert207aboveground biomass to root biomass. A carbon fraction in the biomass of 0.47 is assumed208[11]. It was assessed that the new SRCs accumulate 9.3-27.8 t ha⁻¹ of C after 20 years when209belowground biomass is included and when the carbon loss from conversion is not taken into210account (8 t ha⁻¹ of C). Therefore, the conversion produces a net C sequestration in living211biomass of 0.06-1.0 t ha⁻¹ y⁻¹ or a sequestration of 0.4-2.0 t y⁻¹ over the entire area.

212

213 2.3 BIOMASS FOR TRADITIONAL USE

214

215 Most rural households in Uganda strongly depend on fuel wood and the collection of wood 216 for traditional use (mainly cooking) significantly contributes to deforestation and forest 217 degradation in Uganda [8] [17]. Additional plantations may be used to cover a share of this traditional demand for wood. Using the Anaka IDP camp and the district of Gulu as examples, 218 219 we assess the area of additional plantations needed to supply sufficient wood for traditional 220 use without causing deforestation or degradation of existing forests, i.e. make the use of wood 221 sustainable and help avoiding GHG emissions to the atmosphere. Maintaining the balance 222 between annual forest growth and annual fellings of wood is one of the major indicators of the 223 sustainability concept [18]. When supplying energy from wood in Uganda, it is assumed that 224 the concept of sustainability can be translated as *renewability* of the energy source. 225 As a first step, data on wood demand are compared to the biomass growth of natural resources 226 to assess the fraction of non-renewable biomass extracted in the study area. We define the non-renewable biomass fraction, $FRAC_{NRB}$ as the fraction of wood removals exceeding the 227 228 vegetation growth on total removals:

229 (2)
$$FRAC_{NRB} = \frac{(BD - G)}{BD}$$

Where:

231 *BD*: biomass demand in a certain area $(t y^{-1})$

232 G: biomass growth in the same area (t y^{-1})

233

Second, the emissions caused by the non-renewable biomass extracted annually are calculated by converting the non-renewable biomass to CO_2 emissions. A wood carbon fraction of 0.47 is assumed. Therefore, each tonne of non-renewable biomass burnt releases 1.83 t of CO_2 in the atmosphere.

Third, the area of plantations needed to substitute the non-renewable biomass and to avoid the related emissions is calculated. The plantation area needed depends on the productivity, the amount of fuelwood that can be extracted from the total biomass and the rotation length of the plantation. The area is estimated by assuming that plantations are similar to the Eucalyptus SRCs previously described with an average productivity of 10 t ha⁻¹ y⁻¹ on an oven dry basis. It is assumed that the total demand of wood in the region remains constant over time and that the renewable fraction of wood is still supplied by natural wood resources.

The non-renewable biomass fraction is assessed for the entire Gulu district and for the AnakaIDP camp by using the two following alternative methods.

247 The Amuru district was still part of the Gulu district before 2006 and the available statistics

248 refer to the old administrative borders. Therefore, the assessment of the $FRAC_{NRB}$ is done for

249 Gulu and it includes the area of Amuru. The non-renewable biomass fraction in the Gulu

250 district is assessed by using national removal statistics by FAO, representing the demand, and

biomass growth data from the National Biomass Study (NBS) of Uganda [8].

252 Since data on wood removals are not available at the regional level, the national statistics are

regionalized to assess the amount of wood demand in Gulu. The fuelwood demand is strongly

related to the population residing in a certain area. Therefore, the proportion of the national

255 amount of fuelwood extracted in Gulu is calculated by using the percentage of the population 256 in the district (2%). The industrial roundwood extraction in Gulu, instead, is assessed by 257 calculating the proportion of forest biomass in the district of the total forest biomass in 258 Uganda and by assuming that the percentage of industrial roundwood removed would be the 259 same. The wood removals are converted to total biomass with IPCC default factors [11]. 260 The biomass growth is calculated based on information from the NBS of Uganda (Table 2). 261 The total annual growth is equal to the aboveground annual increment converted to total 262 biomass. Also in this case, we used IPCC default factors.

263

264 Table 2

265

Alternatively, the $FRAC_{NRB}$ is assessed also for the area around the Anaka IDP camp by using a second method. In this area, the fuelwood demand is calculated based on a wood consumption of 601-692 kg of fuelwood per capita [19] [20] and the Anaka population of 22,450 people. Based on these data, it is calculated that the total fuelwood demand in Anaka is 13,500 to 15,500 t y⁻¹. The fuelwood demand is converted to biomass affected by harvesting with IPCC conversion factors.

A land use map of the study area and the National Biomass Study (NBS) data on the biomass growth are used to estimate the biomass resources available to the IDP camp. Fuelwood is collected within a certain walking distance usually of one kilometre, but people can cover a 20 km distance if needed. Three different areas with radii from the IDP camp of 5 km, 10 km and 15 km respectively are selected to calculate the available amount of wood within variable distances and $FRAC_{NRB}$ (Figure 2). It is assumed that all the wood collected or purchased is available within these distances.

279

280 Figure 2

282 3 RESULTS

283

284 3.1 BIOMASS FOR ELECTRICITY GENERATION

285

286 The GHG Balance shows that the wood gasification system produces less GHG emissions 287 than the reference fossil fuel system of diesel generators (Figure 3). When the plantation productivity is low (5 t $ha^{-1} y^{-1}$), the gasification system produces about half of the GHG 288 289 emissions produced by the fossil fuel system (51%). The emissions are even lower if SRCs 290 have higher productivity, i.e. if the average carbon stock of the SRCs is higher. When the plantation produces 15 t $ha^{-1} y^{-1}$ of wood, the installation of a gasifier produces about 1/3 of 291 the emissions produced by diesel generators. Therefore, the gasification system saves 18.1-292 24.6 t y^{-1} or 0.61-0.83 t MWh⁻¹ of CO₂-eq. emissions. 293

294

295 Figure 3

296

The overall GHG balance of the gasification system is given by different components (Figure 4). Emissions are produced by the management of SRCs (harvesting, fertilization, transport of workers and seeds), the transport of wood, the gasifier (construction material, diesel for the operation of the system), and the construction and operation of the electricity grid. These emissions are partially offset by carbon sequestration due to conversion from grasslands to Eucalyptus plantations (Land Use Change). The extent to which emissions are offset depends on the productivity of the plantations.

304

305 Figure 4

307 3.2 BIOMASS FOR TRADITIONAL USE

308

309	The National Biomass Study (NBS) clearly shows that the biomass stock of natural wood
310	resources is decreasing all over Uganda. The trend is mainly caused by the gap between the
311	high demand for fuelwood and the biomass increment [8].
312	By regionalising the national statistics, it is assessed that 722,000 m ³ of fuelwood and 19,100
313	m ³ of roundwood were removed in Gulu in 2005. By converting these figures to total
314	biomass, it is estimated that 4.84 Mt y^{-1} of biomass was harvested or 3.23 Mt y^{-1} when only
315	aboveground biomass is considered. From the supply side, we calculate that the total annual
316	biomass growth in Gulu is equal to 3.82 Mt y^{-1} (2.55 Mt y^{-1} aboveground growth).
317	Based on these numbers, the non-renewable fraction of biomass extracted in Gulu ($FRAC_{NRB}$)
318	is 21.1%.
319	
320	Similar results are produced for the Anaka IDP camp with the alternative approach described
321	in the Methods.
322	The difference between biomass demand in Anaka and biomass produced on land around the
323	camp shows that the net biomass balance is negative within a distance of 10 km radius from
324	the IDP camp. If the biomass would be extracted homogenously in the 15 km radius area, the
325	fuelwood extracted would be all renewable, but within a 15 km radius there is higher
326	competition of use with other settlements (Figure 2). The percentage of non-renewable
327	biomass that is extracted ranges between 88-89% in the 5 km radius to 18-29% in the 10 km
328	radius (Table 3).
329	

330 Table 3

The non-renewable biomass extracted for fuelwood around the Anaka camp produces an
annual amount of CO₂ emissions equal to:

- $151.5 177.6 \times 10^3 \text{ t y}^{-1}$ if fuelwood is collected within 5 km; or 7.3 t y⁻¹ per capita on average.
- $31.6 57.8 \ge 10^3 \ge y^{-1}$ if fuelwood is collected within 10 km; or 2.0 t y⁻¹ per capita on average.

• zero CO₂ emissions if fuelwood is collected within 15 km.

These results do not take into account that biomass is declining and that the percentage ofnon-renewable biomass increases with time.

341 In the Gulu district, the calculated 21% of non-renewable biomass releases each year 1.76 Mt

342 of CO₂ emissions in the atmosphere. These emissions could be avoided by promoting the

343 establishment of dedicated plantations or tree farming (e.g. trees around fields) that would

344 substitute the use of non-renewable biomass.

345 By assuming a productivity of 10 t ha⁻¹ y⁻¹, and a per capita fuelwood demand of 647 kg y⁻¹,

346 the required plantation area is 1283 ha within a 5 km radius for a $FRAC_{NRB}$ of 88%, while

only 348 ha would be required within a 10 km radius for a $FRAC_{NRB}$ of 24%.

348 The use of wood in the area would change from unsustainable use to sustainable use due to

349 the additional wood supply from these plantations.

350 Based on the results from the GHG Balance for the wood gasifier, it can be conservatively

- assumed that the balance between carbon sequestration and emissions due to installation and
- 352 management of the plantations is zero.

353

354 3.3 EFFICIENCY IN PRODUCING EMISSIONS SAVINGS

356	The previous sections showed that fast growing plantations could help achieving GHG
357	emission reductions in rural Uganda either if the wood is used to produce electricity or as
358	fuelwood. The efficiency of these two activities in producing emission savings can be
359	compared by calculating the emission reductions achievable on a per hectare basis.
360	A) Gasification system
361	The gasification system saves on average 21.3 t y^{-1} of CO ₂ -eq. (18.1-24.6 t y^{-1}) compared
362	to diesel generators by planting a total area of 3 ha of SRCs. Therefore the emissions
363	saved by the gasifier are equal to 7.1 t y^{-1} per hectare of SRCs.
364	B) Fuelwood production
365	A fuelwood demand of 14,515 t y ⁻¹ annually required for the Anaka IDP camp produces
366	44,680 t y^{-1} of CO ₂ emissions if the fuelwood is converted to total biomass extracted
367	within a distance of 10 km radius from the camp ($FRAC_{NRB}=24\%$). The total area of SRCs
368	needed to offset these emissions is equal to 348 ha, meaning that the plantations for
369	fuelwood save 128.2 t ha ⁻¹ y ⁻¹ of CO ₂ -eq emissions. The same result in terms of GHG
370	saving per hectare is obtained when fuelwood is extracted within an area of 5 km radius
371	from the camp.
372	Therefore, in terms of GHG savings on a per hectare basis, the most efficient use of fast
373	growing plantations in rural Uganda is to replace fuelwood collected in forests managed
374	unsustainably. However, the services provided by the gasification system and the fuelwood
375	plantations are very different. Even if replacement of fuelwood is much more efficient from
376	the point of view of GHG savings per hectare, the electricity services provided by the
377	gasification system bring additional benefits (e.g. social development) that might render the
378	use of plantations for electricity production more beneficial from a socio-economic point of
379	view. The great difference of GHG savings might also depend on the IPCC factors that
380	convert fuelwood to total biomass. According to these factors and the calculations made, the

- 381 collection of fuelwood from natural wood resources is very inefficient, i.e. the amount of
- 382 biomass affected by harvesting is 3.2 to 8.1 times higher than the amount used for fuelwood
- 383 (the highest factor of 8.1 is for woodlands). In fact, only certain parts of the trees are collected
- for fuelwood, but the remaining biomass of the harvested tree remains in the field and starts to
- decay. Under a more efficient use, when most of the aboveground biomass from natural wood
- resources is used for fuelwood (about 70%) the CO₂ savings would be around 50 t ha⁻¹ y⁻¹.

390 According to the results in this study, wood gasification for electricity production could 391 provide a valid alternative in terms of GHG impacts to diesel generation in rural communities 392 in Uganda. The overall carbon balance shows that wood gasification could provide energy in 393 rural communities that produces at least 50% less GHG emissions than the traditional diesel 394 generators. The GHG balance improves if the productivity of the plantations increases. 395 The productivity of plantations is dependent on the tolerance of the tree species to local 396 climate conditions and to the mortality rate due to fires and pests. In Amuru a short-term trial 397 study showed that the productivity of Eucalyptus in the area could be very low and that a high 398 mortality rate can occur because of fire, low peaks of rainfall and pests [7]. However, more 399 detailed information would be needed to state that Eucalyptus is unsuitable in the study area. 400 Alternative species to E. grandis more adapted to the Amuru area or hybrid Eucalyptus clones 401 that are more resistant to dry conditions, such as *E. grandis x E. camaldulensis*, could be used. 402 In addition, a different management, such as a different rotation length and tree density, could 403 strongly influence the productivity of the SRCs. 404 Another parameter that should be considered to choose suitable tree species is its water use. It 405 is recognized that Eucalyptus is a species that can produce high evapotranspiration. If planted 406 on large scale areas, Eucalyptus could have negative impacts on the water balance in the

407 catchment and limit water availability [21]. This problem should be addressed especially in

408 zones, such as major parts of Africa, where scarcity of water for human consumption is an

409 important issue.

410 We investigated the possibility to plant a native species such as *Markhamia lutea*, but data on

411 its productivity were not robust enough to be used in the study. The use of native species

412 could have the advantage to be more resistant to local conditions and therefore guarantee a

413 more constant and secure wood supply. In addition negative effects on biodiversity and water414 balance could be avoided.

415 Major limits to the presented results emerge from the uncertainty of the input data. As 416 illustrated in the previous paragraphs, more precise information on the productivity of the 417 plantations could narrow down the variability of the final results. Emissions or removals in 418 the soil pool from land conversion should also be included, whereas they were neglected in 419 this study due to the lack of more specific data for similar regions. In addition, large part of 420 the input data to the model GEMIS were not specific for Uganda. A further limit of the study 421 is that we focused only on the GHG impact of the gasification system. A complete 422 environmental impact assessment, including more impact categories, would improve the 423 understanding of the sustainability of such systems. Factors that affect the feasibility of 424 implementation of gasification systems in rural areas should also be taken into account. 425 Barriers to technical implantation could be: mechanical and technical problems when running 426 the gasification system, unavailability of dried and chipped wood and social problems [22]. 427 Moreover, public and private investments that provide the initial capital to establish the 428 gasification system and the plantations should be identified to evaluate the feasibility of such 429 installations (e.g. soft loans, microcredits, Clean Development Mechanism projects) [23]. 430 This study encourages further investigations of social, economic and technical viability of 431 such small scale biomass gasification systems for rural electricity production in Uganda. 432 Small-scale biomass gasification systems providing basic electricity services can have many 433 economic and social advantages towards other renewable and non-renewable electricity 434 sources and often constitute the only current economic alternative to diesel generators in rural 435 Uganda. As little as 68 kg of dry wood per capita and year can already provide significant 436 increases in life standards for rural residents in Uganda when used for electricity generation 437 thus keeping the additional environmental pressures low [9].

439	The study assessed that the present use of wood for fuel in Amuru district is most likely
440	unsustainable. However, the background data are highly uncertain, in particular the data on
441	removals and the conversion factors to assess the total biomass affected by fuelwood
442	extraction. It is also likely that a significant share of the wood removals is not reported by
443	official statistics. If this is the case, the gap between wood removals and forest growth would
444	be higher. Consequently the non-renewable fraction of biomass would be higher than the one
445	estimated in this study and a larger area of plantations would be needed. In addition, the study
446	does not take into account that the non-renewable fraction of biomass will increase over time
447	if natural wood resources will continue to shrink. On these grounds, the estimates of $FRAC_{NRB}$
448	should be considered conservative. On the other hand, conversion factors to assess the total
449	biomass affected by fuelwood extraction might overestimate $FRAC_{NRB}$.
450	Since wood will still be the main source of energy in Uganda, at least in the short to medium
451	term, solutions to decrease pressure on natural resources should be proposed, including the
452	increase of wood resources through additional forest plantations. An alternative to plantations
453	is the increase of energy use efficiency through, e.g., the use of improved wood stoves.
454	However, it is reported that increased efficiency does not necessarily lead to a decrease of
455	wood consumption [2]; this phenomenon is known as the Jevons paradox [24].
456	An additional problem linked to the use of woody biomass is indirect land use change. When
457	plantations are established on land that would have been used for other purposes, it is possible
458	that the other uses are displaced somewhere else. The displacement can produce land use
459	changes elsewhere and consequent negative environmental impacts (e.g. GHG emissions,
460	biodiversity loss). For this reason, we suggested to establish the plantations on areas
461	extensively used or that are marginal (grasslands). However, re-distribution of land after the

- 462 civil war could re-convert large areas to agricultural use and compete with the establishment
- 463 of new plantations.

The establishment of new tree plantations for energy production could be beneficial for rural
communities in Uganda for both GHG emission reductions and the sustainability of biomass
supply.

470 The analysis of the GHG benefits of a small-scale gasification system showed that it would be 471 a valid alternative in terms of GHG impact to the diesel generators for areas that will not have 472 access to hydropower or other forms of electricity generation in the short to medium term due 473 to their distance to established electricity grids, low population density, and biophysical and geographical features. Wood gasification could provide electricity for basic community 474 475 services by planting less than 10 hectares of new Short Rotation Coppices and it could save 476 50-67% of the CO₂-eq.emissions produced by traditional diesel based electricity generators (18.1-24.6 t y⁻¹ or 0.61-0.83 t MWh⁻¹). 477

478 Wood plantations should also be considered to reduce pressure on natural resources due to 479 traditional use of wood in households in Uganda. It was assessed that the fuelwood removals 480 in a rural area in Uganda are unsustainable because the demand for wood exceeds the annual 481 growth from existing forests and other wooded lands. This situation substantially contributes 482 to the degradation of natural biomass resources and, as a consequence, to GHG emissions. 483 The non-renewable fraction of biomass that is extracted (21% in the Gulu district) could be 484 replaced with wood from new plantations to render the overall balance of fuelwood removals 485 sustainable and reduce emissions to the atmosphere. It was assessed that 0.02-0.06 ha per 486 capita of plantations in a rural community in Uganda could avoid the GHG emissions 487 produced through unsustainable extraction of wood (approximately 2.0-7.3 t of CO₂ per capita 488 per year).

490 ACKNOWLEDGEMENTS:

- 491 The authors wish to thank Maximilian Lauer from JOANNEUM RESEARCH for his advice
- 492 on the practical implementation of wood gasification systems in developing countries.

493 [APPENDIX]

REFERENCES

[1] MEMD. Annual Report 2008 [Internet]. Kampala: Editorial Committee of Ministry of Energy and Mineral Development; 2009 [cited 2011 Jun 6]. Available from: http://www.energyandminerals.go.ug/

[2] Gore CD. Power and Process: The Politics of Electricity Sector Reform in Uganda [dissertation]. Toronto, Canada: Department of Political Science, University of Toronto; 2008.

[3] FAO. Global Forest Resource Assessment 2005. Rome, Italy: Food and Agriculture Organization of the United Nations; 2006. 320 p. Forestry Paper: 147.

[4] Nguyena TLT, Hermansena JE, Sagisaka M. Fossil energy savings potential of sugar cane bio- energy systems. Appl Energ 2009;86(supp 1):S132-9.

[5] Abbasi T, Abbasi SA. Biomass energy and the environmental impacts associated with its production and utilization. Renew Sust Energ Rev 2010;14(3):919-37.

[6] FAO [Internet]. Rome, Italy: CLIMWAT 2.0 for CROPWAT [cited 2011 Jun 24]. Available from: <u>http://www.fao.org/nr/water/infores_databases_climwat.html</u>

[7] Seebauer M. Uganda Research Trial Study - Analysis of the Eucalyptus trials in Amuru district, northern Uganda. Freiburg, Germany: Unique Forestry Consultant GmbH; 2009. Contract No.: ENV/2007/114431. Funded by EuropeAid of the European Commission.

[8] Drichi P. National Biomass Study Technical Report of 1996-2002. Kampala, Uganda:

Forest Department, Ministry of Water Lands and Environment; 2002. 118 p.

[9] Buchholz T, Da Silva I. Potential of distributed wood-based biopower systems serving basic electricity needs in rural Uganda. Energ Sustain Dev 2010;14(1):56-61.

[10] Cherubini F, Bird DN, Cowie A, Jungmeier G, Schlamadinger B, Woess-Gallasch S. Energy- and greenhouse gas-based LCA of biofuel and bioenergy systems: key issues, ranges and recommendations. Resour Conserv Recy 2009;53(8):434-47

[11] IPCC. 2006 IPCC Guidelines for National Greenhouse Gas Inventories. Volume 4. Agriculture, Forestry and Other Land Uses. Prepared by the National Greenhouse Gas Inventory Programme, Eggleston HS, Buendia L, Miwa K, Ngara T and Tanabe K, editors. Japan: IGES; 2006.

[12] Fritsche UR, Schmidt K. Global Emission Model of Integrated System (GEMIS) -

Manual. Darmstadt, Germany: Öko-Institut; 2008.

[13] Buchholz T, Volk T. Designing short-rotation coppice based BIOenergy SYstems for Rural Communities in east Africa (BIOSYRCA) - Final report. Syracuse (NY): State University of New York; 2007. 35 p.

[14] Buchholz T, Da Silva I, Volk T, Tennigkeit T. Economics of a Gasification Based Mini
Grid - A Case Study of a 10 kW Unit in Uganda. Proceedings of the Industrial and
Commercial Use of Energy Conference; 2007 May 29-30; Cape Town, South Africa. p. 1259.

[15] Jocovelli P, Milligan B, Amumpe A, Nalwadda C, Kakungulu Z, Odeke C, Atuyamba A, Businge T. Tree planting guidelines for Uganda [Internet]. Kampala, Uganda: SPGS; 2009
[cited 2011 Jun 25]. Available from: <u>http://www.sawlog.ug/</u>

[16] Epron D, Marsden C, M'Bou AT, Saint-André L, d'Annunzio R, Nouvellon Y. Soil carbon dynamics following afforestation of a tropical savannah with Eucalyptus in Congo. Plant Soil 2009;323(1-2):309-22.

[17] Kayanja FIB, Byarugaba D. Disappearing forests of Uganda: The way forward. Curr Sci 2001;81(8):936-47.

[18] Forest Europe. Resolution H1 - General Guidelines for the Sustainable Management of Forests in Europe [Internet]. Helsinki, Finland: Second Ministerial Conference on the Protection of Forests in Europe, Jun 16-17 1993 [cited 2012 Mar 2012]. Available from: www.foresteurope.org/eng/Commitments/Ministerial_Conferences/

[19] Buyinza M, Teera J. A system approach to fuelwood status in Uganda: a demand supply nexus. Res J Appl Sci 2008;3(4):264-75.

[20] Naughton-Treves L, Chapman CA. Fuelwood resources and forest regeneration on fallow land in Uganda. J Sustain Forest 2002;14(4):19-32.

[21] Farley KA, Jobbagy EG, Jackson RB. Effects of afforestation on water yield: a global synthesis with implications for policy. Glob Change Biol 2005;11(10):1565-76.

[22] Ravindranath NH, Somashekar HI, Dasappa S, Jayasheela Reddy CN. Sustainable biomass power for rural India: case study of biomass gasifier for village electrification. Curr Sci 2004;87(7):932-41.

[23] Nuoni MR, Mullick SC, Kandpal TC. Biomass gasifier projects for decentralized power supply in India: A financial evaluation. Energ policy 2007;35(2):1373-85.

[24] Brookes L. The greenhouse effect: the fallacies in the energy efficiency solution. Energ Policy 1990:18(2):199-201.

TABLES

Technology	Efficiency	Life span	Operation	Capacity	Steel	Concrete
			hours			
	(%)	(y)	$(h y^{-1})$	(kW)	(kg)	(kg)
Wood gasifier ^a	15	15	3.257	9	500	200
(bioenergy system)						
Diesel generator ^b	28	10	3.257	3	100	-
(Reference system)						

Table 1 – Basic data on the power generation systems

^aType Ankur Gasifier WBG-15/GAS-9; data according to [12] and expert judgment.

^bDecentralized units in the main buildings type PRAMAC P4500-PF322SYA; data according to product specification (<u>www.pramac.com</u>)

Table 2 – Data on vegetation types in the Gulu District. The data refer only to the aboveground biomass (source: NBS)

Vegetation	Area	Bior	mass	Biomass change		Biomass increment	
	km ²	kt	t ha ⁻¹	kt y ⁻¹	%	t ha ⁻¹ y ⁻¹	kt y ⁻¹
Forest	8	99	131.0	-0.2	-0.2	13.0	9.8
Woodland	4686	14363	30.6	-737.5	-5.1	5.0	2343.1
Bushland	359	420	11.7	-13.6	-3.2	1.0	35.9
Grasslands	1624	1801	11.1	-3.4	-0.2	1.0	162.4
Total	6677	16683	25.0	-754.6	-4.5	n.a.	2551.2

Table 3 – Fraction of non-renewable biomass removed within a certain distance from the Anaka IDP camp. The ranging values are determined by different fuelwood demands per capita.

	15 km	10 km	5 km		
Fuelwood demand (kt y ⁻¹)		13.5 - 15.5			
Tot biomass demand (kt y^{-1})	100.4 - 115.6				
Biomass growth (kt y ⁻¹)	198.5	82.1	12.5		
Net biomass balance (1000 t y ⁻¹)					
- Low	98.0	-18.3	-87.9		
- High	82.9	-33.5	-103.1		
$FRAC_{NRB}(\%)$					
- Low	0	18	88		
- High	0	29	89		

APPENDIX

Inventory table for the wood gasification systems

	Unit	Eucalyptus	Eucalyptus
		15 t	5 t
SRC Cultivation and			
Harvesting			
INPUT			
Auxiliary energy	NAXX71 NAXX71 -1	0.0014	0.0000
Diesel	MWh MWh ⁴	0.0014	0.0029
Petrol	MWh MWh ⁺	0.004	0.012
Auxiliary material	1	0.000	0.050
Engine Oil	kg MWh ¹	0.083	0.250
Phosphate	kg MWh ⁻¹	0.05	0.15
Herbicides	kg MWh ⁻¹	0.01	0.04
OUTPUT			
Eucalyptus	1 1		
Yield (fresh matter)	t ha ⁻¹ y ⁻¹	154	51
Water Content	%	41.5	41.5
Heating Value	$MWh t^{-1}$	2.64	2.64
SRC Transport			
Vehicle Type		Small Truck	
Loading Capacity	t	3.5	
Fuel Consumption	$dm^3 km^{-1}$	0.165	
Distance	km	60	
Gasifier			
INPUT			
Eucalyptus	$MWh MWh^{-1}$	4.87	
Auxiliary energy			
Diesel	$MWh MWh^{-1}$	1.79	
Construction material			
Steel	$t MW^{-1}$	56	
Concrete	$t MW^{-1}$	22	
OUTPUT			
Electricity			
Power Grid			
Transmission Losses	% km ⁻¹	0.04	
Construction material			
Steel	t km ⁻¹	550	
Concrete	t km ⁻¹	45	

FIGURE CAPTIONS

Figure 1 – Process chains for the centralized wood gasification system and the fossil reference system with decentralized diesel generators.

Figure 2 – Land use map of the water catchment in which the Anaka camp is located [8]. The dotted circles around the camp define the wood supply areas within variable distances.

Figure 3 – Comparison of GHG emissions from the diesel generators (E-DG) and the wood gasifier (E-WG). The emissions from the gasifier are shown for different levels of productivity of the plantations (5 and 15 t $ha^{-1} y^{-1}$).

Figure 4 – Emission components of the gasification system (E- WG) according to different productivities of the Short Rotation Coppices (SRCs).

Gasification system

Diesel Generator



Process Steps

